

屋内照明器具特性	
品番 (品名)	P A 4 0 1 5 0 C L N 3 5
光源	LED3500_70_1515 ×1 1515.0 l m
管理番号	K0177950 (0) DR 1
B Z 分類	B Z 2

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 7	0 . 6	6 7	5 8	5 1	4 7	6 6	5 7	5 1	4 7	6 4	5 6	5 1	4 7	6 3	5 5	5 0	4 7	4 5
			0 . 6 3	0 . 8	7 7	6 8	6 2	5 8	7 6	6 8	6 2	5 8	7 4	6 7	6 1	5 8	7 2	6 6	6 1	5 7	5 6
			1 . 0	8 3	7 5	7 0	6 5	8 2	7 5	6 9	6 5	8 0	7 3	6 9	6 5	7 8	7 2	6 8	6 5	6 3	
			0 . 5 6	1 . 2 5	8 8	8 1	7 6	7 2	8 7	8 1	7 6	7 2	8 5	7 9	7 5	7 1	8 2	7 8	7 4	7 1	6 9
下方投影面積		c m ²	1 . 5	9 2	8 5	8 1	7 7	9 0	8 5	8 0	7 7	8 8	8 3	7 9	7 6	8 6	8 2	7 8	7 5	7 3	
			等価発光面積	c m ²	2 . 0	9 6	9 1	8 7	8 3	9 5	9 0	8 6	8 3	9 2	8 8	8 5	8 2	9 0	8 7	8 4	8 1
取付 高さ	器具間隔最大限		2 . 5	9 8	9 4	9 1	8 8	9 7	9 3	9 0	8 7	9 5	9 1	8 9	8 6	9 2	9 0	8 7	8 5	8 3	
	横方向 (A)	縦方向 (B)	3 . 0	1 0 0	9 7	9 3	9 1	9 9	9 6	9 3	9 0	9 6	9 4	9 1	8 9	9 4	9 2	9 0	8 8	8 6	
1 . 5 m	1 . 6 1 m	2 . 1 6 m	4 . 0	1 0 2	9 9	9 7	9 5	1 0 1	9 8	9 6	9 4	9 9	9 6	9 5	9 3	9 6	9 5	9 3	9 1	8 9	
2	2 . 1 3	2 . 6 4	5 . 0	1 0 3	1 0 1	9 9	9 7	1 0 2	1 0 0	9 8	9 7	1 0 0	9 8	9 7	9 5	9 8	9 6	9 5	9 4	9 1	
2 . 5	2 . 6 5	3 . 1 5	7 . 0	1 0 5	1 0 3	1 0 2	1 0 0	1 0 4	1 0 2	1 0 1	9 9	1 0 1	1 0 0	9 9	9 8	9 9	9 8	9 7	9 6	9 3	
3	3 . 1 7	3 . 6 8	1 0 . 0	1 0 6	1 0 5	1 0 4	1 0 3	1 0 5	1 0 4	1 0 3	1 0 2	1 0 2	1 0 2	1 0 1	1 0 0	1 0 0	9 9	9 9	9 8	9 5	

