

屋内照明器具特性	
品番 (品名)	P ML L 1 0 2 5 4 K 5 0
光源	LED5000_70_260 ×1 260.0 l m
管理番号	K0178333 (0) DY 1
B Z 分類	BZ5 / 0.7 / BZ4 / 2.3 / BZ5

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		8 % 9 2 %	室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 6 9	0 . 6	5 7	4 5	3 7	3 2	5 5	4 4	3 7	3 2	5 2	4 2	3 6	3 1	4 9	4 1	3 5	3 0	2 8	
			0 . 6 7	0 . 8	6 7	5 5	4 8	4 2	6 5	5 4	4 7	4 2	6 1	5 2	4 6	4 1	5 8	5 0	4 4	4 0	3 7	
			0 . 6 3	1 . 0	7 3	6 3	5 5	5 0	7 1	6 1	5 4	4 9	6 7	5 9	5 3	4 8	6 3	5 6	5 1	4 7	4 4	
				1 . 2 5	7 9	6 9	6 2	5 7	7 7	6 8	6 1	5 6	7 2	6 5	5 9	5 5	6 9	6 3	5 8	5 4	5 0	
下方投影面積		c m ²	1 . 5	8 3	7 4	6 8	6 2	8 0	7 3	6 6	6 2	7 6	7 0	6 4	6 0	7 2	6 7	6 2	5 8	5 5		
等価発光面積			c m ²	2 . 0	8 8	8 1	7 5	7 0	8 6	7 9	7 4	6 9	8 1	7 6	7 1	6 7	7 7	7 3	6 9	6 6	6 2	
取付高さ	器具間隔最大限		2 . 5	9 1	8 5	8 0	7 6	8 9	8 4	7 9	7 5	8 5	8 0	7 6	7 2	8 1	7 7	7 3	7 0	6 6		
	横方向 (A) 縦方向 (B)		3 . 0	9 4	8 8	8 4	8 0	9 1	8 7	8 2	7 9	8 7	8 3	7 9	7 6	8 3	8 0	7 7	7 4	7 0		
H m	1 . 2 5 H m 1 . 2 5 H m		4 . 0	9 7	9 2	8 9	8 5	9 4	9 1	8 7	8 4	9 0	8 7	8 4	8 1	8 6	8 3	8 1	7 9	7 4		
			5 . 0	9 9	9 5	9 2	8 9	9 6	9 3	9 0	8 7	9 2	8 9	8 7	8 4	8 8	8 6	8 4	8 2	7 7		
			7 . 0	1 0 1	9 8	9 5	9 3	9 8	9 6	9 4	9 2	9 4	9 2	9 0	8 8	9 0	8 9	8 7	8 5	8 1		
			1 0 . 0	1 0 2	1 0 0	9 8	9 7	1 0 0	9 8	9 7	9 5	9 6	9 4	9 3	9 2	9 2	9 1	9 0	8 8	8 3		

