

屋内照明器具特性	
品番 (品名)	L G W8 5 0 3 5 B
光源	L D A 7 L - H / S / 6 × 1 8 1 0 . 0 l m
管理番号	K 0 1 7 8 5 2 7 (0) D R 1
B Z 分類	B Z 4

器具効率		19 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01)																				ZCM
保守率		良 中 否	0.63	0.6	11	9	7	6	11	9	7	6	10	8	7	6	10	8	7	6	6				
			0.6	0.8	13	11	9	8	12	11	9	8	12	10	9	8	12	10	9	8	8				
			0.56	1.0	14	12	11	10	14	12	11	10	13	12	11	10	13	11	10	10	9				
				1.25	15	13	12	11	15	13	12	11	14	13	12	11	14	13	12	11	11				
下方投影面積		c m ²	1.5	16	14	13	12	15	14	13	12	15	14	13	12	14	13	13	12	11					
等価発光面積			c m ²	2.0	17	15	14	14	16	15	14	14	16	15	14	13	15	15	14	13	13				
取付 高さ	器具間隔最大限			2.5	17	16	15	15	17	16	15	15	16	16	15	14	16	15	15	14	14				
	横方向 (A)		縦方向 (B)	3.0	18	17	16	15	17	17	16	15	17	16	16	15	16	16	15	15	14				
H m	1.14 H m		1.10 H m	4.0	18	18	17	16	18	17	17	16	17	17	16	16	17	17	16	16	15				
				5.0	19	18	17	17	18	18	17	17	18	17	17	17	17	17	17	16	16				
				7.0	19	18	18	18	19	18	18	18	18	18	18	17	18	17	17	17	16				
				10.0	19	19	19	18	19	19	18	18	18	18	18	18	18	18	18	17	17				

