

屋内照明器具特性	
品番 (品名)	LGD9100K
光源	LLD3020LCE1 ×1 795.0 lm
管理番号	K0175529 (2) DR1
BZ分類	BZ1

器具効率		88 %	反射率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		0 %	室指数	照明率 (X0.01)																		Z	C		M
下方光束		88 %																							
保守率		良 中 否	0.67	0.6	73	67	64	61	72	67	64	61	71	67	63	61	70	66	63	61	60				
			0.63	0.8	78	73	70	68	78	73	70	67	76	72	69	67	75	71	69	67	66				
			0.56	1.0	82	77	74	72	81	77	74	71	79	76	73	71	78	75	73	71	70				
				1.25	84	80	78	75	84	80	77	75	82	79	76	75	80	78	76	74	73				
下方投影面積		c m ²	1.5	86	83	80	78	85	82	80	78	84	81	79	77	82	80	78	76	75					
等価発光面積			c m ²	2.0	89	86	83	81	88	85	83	81	86	84	82	80	84	82	81	80	78				
取付 高さ	器具間隔最大限		2.5	90	88	86	84	89	87	85	83	87	85	84	82	86	84	83	82	80					
	横方向 (A)		縦方向 (B)	3.0	91	89	87	85	90	88	86	85	88	86	85	84	86	85	84	83	81				
H m	0.41 H m	0.41 H m	4.0	92	90	89	88	91	90	88	87	89	88	87	86	87	86	86	85	83					
			5.0	93	91	90	89	92	90	89	88	90	89	88	87	88	87	86	86	84					
			7.0	93	92	92	91	92	92	91	90	90	90	89	88	89	88	88	87	85					
			10.0	94	93	93	92	93	92	92	91	91	91	90	90	89	89	88	88	86					

