

屋内照明器具特性	
品番 (品名)	L G D 9 1 0 0 K
光源	L L D 4 0 0 0 L C T 1 × 1 8 4 5 . 0 l m
管理番号	K 0 1 8 9 1 2 6 (2) D R 1
B Z 分類	B Z 4 / 0 . 7 / B Z 3

器具効率		83 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X 0 . 0 1) Z C M																				
保守率		良 中 否	0 . 6 7	0 . 6	51	42	36	31	50	41	35	31	48	40	35	31	46	39	35	31	30				
			0 . 6 3	0 . 8	60	51	45	41	58	51	45	41	56	49	45	41	55	49	44	41	39				
			0 . 5 6	1 . 0	65	57	52	48	64	57	52	48	62	56	51	47	60	55	50	47	46				
				1 . 2 5	70	63	58	54	69	62	58	54	67	61	57	54	64	60	56	53	52				
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	73	67	62	59	72	66	62	58	70	65	61	58	68	64	60	57	56					
			2 . 0	77	72	68	65	76	71	68	65	74	70	67	64	72	68	66	63	61					
			2 . 5	80	76	72	69	79	75	71	69	76	73	70	68	74	72	69	67	65					
			3 . 0	81	78	75	72	80	77	74	72	78	75	73	71	76	74	72	70	68					
H m	1 . 2 4 H m	1 . 2 4 H m	4 . 0	83	81	78	76	82	80	78	75	80	78	76	74	78	76	75	73	71					
			5 . 0	85	82	80	78	84	82	80	78	82	80	78	77	80	78	77	75	73					
			7 . 0	86	84	83	81	85	84	82	81	83	82	81	79	81	80	79	78	76					
			1 0 . 0	87	86	85	84	86	85	84	83	84	83	82	82	82	82	81	80	78					

