

屋内照明器具特性	
品番 (品名)	LGD9100K
光源	LLD2020LCT1 ×1 460.0 lm
管理番号	K0189129 (1) DR1
BZ分類	BZ1

器具効率		96 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
上方光束		0 %	室指数	照明率 (X0.01)																		ZCM	
下方光束		96 %																					
保守率		良	0.6	79	73	69	66	78	72	69	66	77	72	68	66	76	71	68	66	65			
		中	0.8	85	79	76	73	84	79	75	73	82	78	75	73	81	77	74	72	71			
		否	0.63	1.0	88	84	80	77	88	83	80	77	86	82	79	77	84	81	79	77	75		
		0.56 <td>1.25</td> <td>91</td> <td>87</td> <td>84</td> <td>81</td> <td>91</td> <td>87</td> <td>84</td> <td>81</td> <td>89</td> <td>85</td> <td>83</td> <td>81</td> <td>87</td> <td>84</td> <td>82</td> <td>80</td> <td>79</td>	1.25	91	87	84	81	91	87	84	81	89	85	83	81	87	84	82	80	79			
下方投影面積		c m ²	1.5	93	90	87	84	93	89	86	84	91	88	85	83	89	87	85	83	81			
等価発光面積			c m ²	2.0	96	93	90	88	95	92	90	88	93	91	89	87	91	89	88	86	85		
取付 高さ	器具間隔最大限		2.5	98	95	93	91	97	94	92	90	95	93	91	89	93	91	90	88	87			
	横方向 (A)		縦方向 (B)	3.0	99	96	94	93	98	95	94	92	96	94	92	91	94	92	91	90	88		
H m	0.41 H m	0.41 H m	4.0	100	98	96	95	99	97	96	94	97	95	94	93	95	94	93	92	90			
			5.0	101	99	98	97	100	98	97	96	97	96	95	94	96	95	94	93	91			
			7.0	101	100	99	98	100	99	98	98	98	97	97	96	96	96	95	94	92			
			10.0	102	101	101	100	101	100	100	99	99	98	98	97	97	96	96	96	93			

