

屋内照明器具特性	
品番 (品名)	L G D 9 1 0 1 K
光源	L L D 5 0 0 0 L C C 1 × 1 1 1 4 0 . 0 1 m
管理番号	K 0 1 8 7 3 0 7 (0) D 1
B Z 分類	B Z 3

器具効率		100 % 上方光束 1 % 下方光束 99 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6	64	54	47	42	63	53	47	42	61	52	46	42	59	51	46	42	40	
			0 . 8	74	65	58	53	73	64	58	53	70	63	57	53	68	61	56	53	51	
			1 . 0	81	72	66	61	79	71	65	61	77	70	64	60	74	68	64	60	58	
			0 . 56	1 . 25	86	78	72	68	84	77	72	68	82	76	71	67	79	74	70	67	65
下方投影面積		c m ²	1 . 5	89	82	77	73	88	82	77	73	85	80	75	72	83	78	74	71	69	
			等価発光面積		c m ²	2 . 0	94	88	84	80	92	87	83	79	90	85	82	79	87	84	80
取付 高さ	器具間隔最大限		2 . 5	97	92	88	84	95	91	87	84	93	89	86	83	90	87	84	82	79	
	横方向 (A) 縦方向 (B)		3 . 0	99	94	91	88	97	93	90	87	94	91	88	86	92	89	87	85	82	
H m	1 . 26 H m	1 . 26 H m	4 . 0	101	98	95	92	100	97	94	91	97	94	92	90	94	92	90	89	86	
			5 . 0	102	100	97	95	101	99	96	94	98	96	94	93	96	94	93	91	88	
			7 . 0	104	102	100	98	103	101	99	97	100	99	97	96	98	96	95	94	91	
			10 . 0	105	104	102	101	104	103	101	100	101	100	99	98	99	98	97	96	93	

