

屋内照明器具特性	
品番 (品名)	L G D 9 1 0 2 K
光源	L L D 4 0 4 0 2 C Q 1 (K A K U S A N) × 1 8 6 0 . 0 1 m
管理番号	K 0 1 8 3 9 4 7 (0) D R 1
B Z 分類	B Z 3

器具効率		75 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						室指数	照明率 (X 0 . 0 1) Z C M															
保守率		良 中 否	0 . 6 7	0 . 6	49	41	36	32	48	40	36	32	46	40	35	32	45	39	35	32	31	
			0 . 6 3	0 . 8	56	49	44	40	55	48	44	40	53	47	43	40	51	46	43	40	38	
			0 . 5 6	1 . 0	60	54	49	46	59	53	49	45	57	52	48	45	56	51	48	45	43	
				1 . 2 5	64	58	54	51	63	58	54	50	61	56	53	50	59	55	52	50	48	
下方投影面積		c m ²	1 . 5	67	61	57	54	66	61	57	54	64	59	56	53	62	58	55	53	51		
等価発光面積				c m ²	2 . 0	70	66	62	59	69	65	62	59	67	64	61	58	65	62	60	58	56
取付 高さ	器具間隔最大限				2 . 5	72	68	65	63	71	68	65	62	69	66	64	62	67	65	63	61	59
	横方向 (A)		縦方向 (B)		3 . 0	74	70	68	65	73	70	67	65	71	68	66	64	69	67	65	63	61
H m	1 . 0 5 H m	1 . 0 5 H m	4 . 0	75	73	71	69	74	72	70	68	72	70	69	67	71	69	67	66	64		
			5 . 0	76	74	72	71	75	74	72	70	74	72	70	69	72	70	69	68	66		
			7 . 0	78	76	75	73	77	75	74	73	75	74	72	71	73	72	71	70	68		
			1 0 . 0	79	78	76	75	78	77	76	75	76	75	74	73	74	73	73	72	70		

