

屋内照明器具特性	
品番 (品名)	L G D 9 1 0 2 K
光源	L L D 4 0 0 0 L C T 1 × 1 8 4 5 . 0 l m
管理番号	K 0 1 8 9 1 3 4 (1) D R 1
B Z 分類	B Z 3

器具効率		6 4 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 7	0 . 6	4 1	3 5	3 0	2 7	4 0	3 4	3 0	2 7	3 9	3 4	3 0	2 7	3 8	3 3	3 0	2 7	2 6
			0 . 6 3	0 . 8	4 7	4 1	3 7	3 4	4 7	4 1	3 7	3 4	4 5	4 0	3 7	3 4	4 4	3 9	3 6	3 4	3 3
			0 . 5 6	1 . 0	5 1	4 6	4 2	3 9	5 0	4 5	4 1	3 9	4 9	4 4	4 1	3 8	4 7	4 3	4 0	3 8	3 7
				1 . 2 5	5 5	5 0	4 6	4 3	5 4	4 9	4 6	4 3	5 2	4 8	4 5	4 2	5 0	4 7	4 4	4 2	4 1
下方投影面積		c m ²		1 . 5	5 7	5 2	4 9	4 6	5 6	5 2	4 8	4 6	5 4	5 1	4 8	4 5	5 3	5 0	4 7	4 5	4 4
			等価発光面積	c m ²	2 . 0	6 0	5 6	5 3	5 0	5 9	5 5	5 2	5 0	5 7	5 4	5 2	5 0	5 5	5 3	5 1	4 9
取付 高さ	器具間隔最大限			2 . 5	6 1	5 8	5 6	5 3	6 0	5 8	5 5	5 3	5 9	5 6	5 4	5 2	5 7	5 5	5 3	5 2	5 0
	横方向 (A) 縦方向 (B)			3 . 0	6 3	6 0	5 7	5 5	6 2	5 9	5 7	5 5	6 0	5 8	5 6	5 4	5 8	5 7	5 5	5 4	5 2
H m	1 . 1 6 H m	1 . 1 6 H m		4 . 0	6 4	6 2	6 0	5 8	6 3	6 1	5 9	5 8	6 2	6 0	5 8	5 7	6 0	5 9	5 7	5 6	5 4
				5 . 0	6 5	6 3	6 2	6 0	6 4	6 3	6 1	6 0	6 3	6 1	6 0	5 9	6 1	6 0	5 9	5 8	5 6
				7 . 0	6 6	6 5	6 4	6 2	6 5	6 4	6 3	6 2	6 4	6 3	6 2	6 1	6 2	6 1	6 0	6 0	5 8
				1 0 . 0	6 7	6 6	6 5	6 4	6 6	6 5	6 4	6 4	6 5	6 4	6 3	6 2	6 3	6 2	6 2	6 1	5 9

