

| 屋内照明器具特性 |                          |
|----------|--------------------------|
| 品番 (品名)  | NTN88081B                |
| 光源       | LLD2020MLCB1 ×1 460.0 lm |
| 管理番号     | K0179234 ( 0 ) DR 1      |
| BZ分類     | BZ1                      |

| 器具効率     | 98 %             | 反射率       | 天井            | 80 % |     |     |     | 70 % |     |     |     | 50 % |     |    |    | 30 % |    |    |    | 0 % |  |     |  |
|----------|------------------|-----------|---------------|------|-----|-----|-----|------|-----|-----|-----|------|-----|----|----|------|----|----|----|-----|--|-----|--|
|          |                  |           | 壁             | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |  |     |  |
|          |                  |           | 床             | 10 % |     |     |     | 10 % |     |     |     | 10 % |     |    |    | 10 % |    |    |    | 0 % |  |     |  |
| 上方光束     | 1 %              | 室指数       | 照明率 ( X0.01 ) |      |     |     |     |      |     |     |     |      |     |    |    |      |    |    |    |     |  | ZCM |  |
| 下方光束     | 97 %             |           |               |      |     |     |     |      |     |     |     |      |     |    |    |      |    |    |    |     |  |     |  |
| 保守率      | 良<br>中<br>否      | 0.69      | 0.6           | 79   | 73  | 69  | 66  | 79   | 72  | 68  | 66  | 77   | 72  | 68 | 66 | 76   | 71 | 68 | 65 | 64  |  |     |  |
|          |                  | 0.67      | 0.8           | 85   | 79  | 75  | 72  | 84   | 79  | 75  | 72  | 83   | 78  | 74 | 72 | 81   | 77 | 74 | 72 | 70  |  |     |  |
|          |                  | 0.63      | 1.0           | 89   | 83  | 80  | 77  | 88   | 83  | 79  | 76  | 86   | 82  | 79 | 76 | 84   | 81 | 78 | 76 | 74  |  |     |  |
|          |                  |           | 1.25          | 92   | 87  | 84  | 81  | 91   | 86  | 83  | 80  | 89   | 85  | 82 | 80 | 87   | 84 | 81 | 79 | 78  |  |     |  |
| 下方投影面積   | c m <sup>2</sup> | 1.5       | 94            | 90   | 86  | 84  | 93  | 89   | 86  | 83  | 91  | 88   | 85  | 83 | 89 | 86   | 84 | 82 | 80 |     |  |     |  |
| 等価発光面積   |                  | 2.0       | 97            | 93   | 90  | 88  | 96  | 92   | 90  | 87  | 94  | 91   | 88  | 86 | 92 | 89   | 87 | 85 | 84 |     |  |     |  |
|          |                  | 2.5       | 99            | 95   | 93  | 91  | 97  | 95   | 92  | 90  | 95  | 93   | 91  | 89 | 93 | 91   | 89 | 88 | 86 |     |  |     |  |
| 取付<br>高さ | 器具間隔最大限          |           | 3.0           | 100  | 97  | 95  | 93  | 99   | 96  | 94  | 92  | 96   | 94  | 92 | 91 | 94   | 92 | 91 | 90 | 87  |  |     |  |
|          | 横方向 ( A )        | 縦方向 ( B ) | 4.0           | 101  | 99  | 97  | 95  | 100  | 98  | 96  | 95  | 98   | 96  | 95 | 93 | 95   | 94 | 93 | 92 | 89  |  |     |  |
| H m      | 0.45 H m         | 0.45 H m  | 5.0           | 102  | 100 | 99  | 97  | 101  | 99  | 98  | 96  | 99   | 97  | 96 | 95 | 96   | 95 | 94 | 93 | 91  |  |     |  |
|          |                  |           | 7.0           | 103  | 102 | 101 | 99  | 102  | 101 | 100 | 98  | 100  | 99  | 98 | 97 | 97   | 96 | 96 | 95 | 92  |  |     |  |
|          |                  |           | 10.0          | 104  | 103 | 102 | 101 | 103  | 102 | 101 | 100 | 100  | 100 | 99 | 98 | 98   | 97 | 97 | 96 | 93  |  |     |  |

