

屋内照明器具特性	
品番 (品名)	NTN88081B
光源	LLD2000LCS1 ×1 580.0 lm
管理番号	K0183294 (0) DR 1
BZ分類	BZ6

器具効率		8 3 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		1 4 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束		6 9 %																				
保守率		良 中 否	0 . 6 9	0 . 6	4 3	3 3	2 6	2 2	4 1	3 2	2 5	2 1	3 8	3 0	2 4	2 0	3 5	2 8	2 3	1 9	1 7	
			0 . 6 7	0 . 8	5 1	4 1	3 4	2 9	4 9	3 9	3 3	2 8	4 5	3 7	3 1	2 7	4 1	3 5	3 0	2 6	2 3	
			0 . 6 3	1 . 0	5 6	4 6	4 0	3 4	5 4	4 5	3 8	3 4	4 9	4 2	3 6	3 2	4 5	3 9	3 4	3 1	2 7	
				1 . 2 5	6 1	5 2	4 5	4 0	5 8	5 0	4 4	3 9	5 3	4 7	4 2	3 7	4 9	4 4	3 9	3 6	3 2	
下方投影面積		cm ²	1 . 5	6 4	5 6	4 9	4 4	6 1	5 4	4 8	4 3	5 7	5 0	4 5	4 1	5 2	4 7	4 3	3 9	3 5		
等価発光面積		cm ²	2 . 0	6 8	6 1	5 6	5 1	6 6	5 9	5 4	5 0	6 1	5 6	5 1	4 7	5 6	5 2	4 8	4 5	4 1		
取付高さ	器具間隔最大限		2 . 5	7 1	6 5	6 0	5 6	6 9	6 3	5 8	5 4	6 4	5 9	5 5	5 2	5 9	5 5	5 2	4 9	4 4		
	横方向 (A) 縦方向 (B)		3 . 0	7 4	6 8	6 3	5 9	7 1	6 6	6 2	5 8	6 6	6 2	5 8	5 5	6 1	5 8	5 5	5 2	4 7		
H m	1 . 2 7 H m	1 . 2 7 H m	4 . 0	7 6	7 2	6 8	6 4	7 4	7 0	6 6	6 3	6 9	6 5	6 2	5 9	6 4	6 1	5 9	5 6	5 1		
			5 . 0	7 8	7 4	7 1	6 8	7 6	7 2	6 9	6 6	7 0	6 8	6 5	6 2	6 6	6 3	6 1	5 9	5 4		
			7 . 0	8 0	7 7	7 5	7 2	7 8	7 5	7 2	7 0	7 3	7 0	6 8	6 6	6 8	6 6	6 4	6 3	5 7		
			1 0 . 0	8 2	8 0	7 8	7 6	7 9	7 7	7 5	7 4	7 4	7 3	7 1	7 0	7 0	6 8	6 7	6 6	6 0		

