

屋内照明器具特性	
品番 (品名)	NTN88081W
光源	LLD4000LCB1 ×1 845.0 lm
管理番号	K0179236 (0) DR 1
BZ分類	BZ5

器具効率		97 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.69	0.6	54	42	34	29	52	41	34	29	50	40	33	29	47	38	33	28	26
			0.67	0.8	63	52	45	39	62	51	44	39	58	49	43	38	56	48	42	37	35
			0.63	1.0	70	59	52	46	68	58	51	46	64	56	50	45	61	54	49	44	41
			0.63	1.25	76	66	59	53	74	65	58	53	70	62	56	52	67	60	55	51	48
下方投影面積		cm ²	1.5	80	71	64	59	78	70	63	58	74	67	61	57	70	65	60	56	53	
			等価発光面積	cm ²	2.0	85	78	72	67	83	76	71	66	79	73	69	65	76	71	67	63
取付 高さ	器具間隔最大限		2.5	88	82	77	72	86	81	76	71	83	78	74	70	79	75	71	68	65	
	横方向 (A) 縦方向 (B)		3.0	91	85	81	76	89	84	79	75	85	81	77	74	82	78	75	72	68	
H m	1.27 H m	1.27 H m	4.0	94	90	86	82	92	88	84	81	88	85	82	79	85	82	79	77	73	
			5.0	96	92	89	86	94	91	87	85	90	87	85	82	87	85	82	80	76	
			7.0	98	95	93	90	96	94	91	89	93	91	89	87	89	88	86	84	80	
			10.0	100	98	96	94	98	96	94	93	94	93	91	90	91	90	89	87	83	

