

屋内照明器具特性	
品番 (品名)	L G B 8 1 8 1 2
光源	LED2700_70_1650 ×1 1650.0 lm
管理番号	K0142374 (0) DR 1
B Z 分類	B Z 6

器具効率	100 % 上方光束 50 % 下方光束 50 %	天井 反射率 壁 床 室指数	80 %				70 %				50 %				30 %				0 %
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
			照明率 (X0.01) Z C M																
保守率	良 0.67 中 0.63 否 0.56	0.6	48	36	29	23	44	34	27	22	37	29	23	19	30	24	20	16	11
		0.8	56	45	37	32	52	42	35	30	43	36	30	26	36	30	25	22	16
		1.0	62	52	44	38	57	48	41	36	48	41	35	31	40	34	30	26	19
		1.25	68	58	50	45	62	54	47	42	52	46	41	36	43	38	34	31	22
下方投影面積 等価発光面積	c m ² c m ²	1.5	72	63	55	50	66	58	52	47	56	49	44	40	46	41	37	34	24
		2.0	77	69	63	57	71	64	59	54	60	55	50	46	50	46	42	39	28
		2.5	81	74	68	63	74	68	63	59	63	58	54	51	52	49	46	43	31
取付 高さ	器具間隔最大限		3.0	83	77	72	67	77	71	67	63	65	61	57	54	54	51	48	33
	横方向 (A) 縦方向 (B)		4.0	86	81	77	73	80	75	71	68	68	64	61	59	56	54	52	36
1.5m	1.25 m	2.08 m	5.0	88	84	80	77	82	78	75	71	69	67	64	62	58	56	54	38
2	1.67	2.7	7.0	90	87	84	81	84	81	78	76	72	69	67	65	60	58	57	40
2.5	2.08	3.33	10.0	92	90	88	85	86	84	82	80	73	72	70	69	62	60	59	42
3	2.5	3.96																	

