

屋内照明器具特性	
品番 (品名)	S P L 5 4 2 9
光源	L L D 2 0 2 0 L C E 1 × 4 4 6 0 . 0 l m
管理番号	K 0 1 8 3 1 0 9 (0) D B 1
B Z 分類	B Z 1

器具効率		8 4 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		8 4 %																					
保守率		良	0 . 6 7	0 . 6	6 9	6 3	6 0	5 8	6 8	6 3	6 0	5 7	6 7	6 2	6 0	5 7	6 6	6 2	5 9	5 7	5 6		
		中	0 . 6 3	0 . 8	7 4	6 9	6 6	6 3	7 3	6 8	6 5	6 3	7 2	6 8	6 5	6 3	7 0	6 7	6 5	6 3	6 2		
		否	0 . 5 6	1 . 0	7 7	7 2	6 9	6 7	7 6	7 2	6 9	6 7	7 5	7 1	6 8	6 6	7 3	7 0	6 8	6 6	6 5		
				1 . 2 5	7 9	7 6	7 3	7 0	7 9	7 5	7 2	7 0	7 7	7 4	7 2	7 0	7 6	7 3	7 1	6 9	6 8		
下方投影面積		c m ²		1 . 5	8 1	7 8	7 5	7 3	8 0	7 7	7 5	7 2	7 9	7 6	7 4	7 2	7 7	7 5	7 3	7 1	7 0		
等価発光面積		c m ²		2 . 0	8 3	8 1	7 8	7 6	8 3	8 0	7 8	7 6	8 1	7 9	7 7	7 5	7 9	7 7	7 6	7 4	7 3		
取付 高さ	器具間隔最大限		2 . 5	8 5	8 2	8 0	7 9	8 4	8 2	8 0	7 8	8 2	8 0	7 9	7 7	8 1	7 9	7 8	7 6	7 5			
	横方向 (A)		縦方向 (B)	3 . 0	8 6	8 4	8 2	8 0	8 5	8 3	8 1	8 0	8 3	8 1	8 0	7 9	8 1	8 0	7 9	7 8	7 6		
H m	0 . 4 1 H m	0 . 4 0 H m	4 . 0	8 7	8 5	8 4	8 2	8 6	8 4	8 3	8 2	8 4	8 3	8 2	8 1	8 2	8 1	8 0	8 0	7 8			
			5 . 0	8 8	8 6	8 5	8 4	8 7	8 5	8 4	8 3	8 5	8 4	8 3	8 2	8 3	8 2	8 1	8 1	7 9			
			7 . 0	8 8	8 7	8 6	8 6	8 7	8 7	8 6	8 5	8 6	8 5	8 4	8 3	8 4	8 3	8 3	8 2	8 0			
			1 0 . 0	8 9	8 8	8 8	8 7	8 8	8 7	8 7	8 6	8 6	8 6	8 5	8 5	8 4	8 4	8 4	8 3	8 1			

