

屋内照明器具特性	
品番 (品名)	L G W5 1 7 7 9 Y
光源	LLD2000LCE1 ×1 531.0 lm
管理番号	K0181600 (0) DR 1
B Z 分類	BZ5 / 0.9 / BZ4 / 6.0 / BZ5 / 8.5 / BZ4

器具効率	70 % 上方光束 0 % 下方光束 70 %	天井	80 %				70 %				50 %				30 %				0 %
		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
		室指数	照明率 (X0.01)																Z CM
保守率	良 0.63	0.6	40	32	26	23	39	31	26	23	38	31	26	22	36	30	26	22	21
	中 0.6	0.8	47	39	34	30	46	39	34	30	44	38	33	30	42	37	33	30	28
	否 0.56	1.0	52	44	39	35	51	44	39	35	49	43	38	35	47	42	38	35	33
		1.25	56	49	44	40	55	49	44	40	53	47	43	40	51	46	43	40	38
下方投影面積 等価発光面積		1.5	59	53	48	44	58	52	48	44	55	51	47	44	53	49	46	43	42
		2.0	63	58	53	50	61	57	53	50	59	55	52	49	57	54	51	49	47
		2.5	65	61	57	54	64	60	57	54	62	58	56	53	60	57	55	52	51
		3.0	67	63	60	57	66	62	59	57	64	61	58	56	62	59	57	55	53
取付高さ	器具間隔最大限		4.0	69	66	63	61	68	65	63	60	66	63	61	60	64	62	60	59
H m	1.22 H m	1.22 H m	5.0	70	68	65	63	69	67	65	63	67	65	64	62	65	64	62	61
			7.0	72	70	68	67	71	69	67	66	69	67	66	65	67	66	65	64
			10.0	73	71	70	69	72	71	69	68	70	69	68	67	68	67	66	64

