

屋内照明器具特性	
品番 (品名)	L G W5 1 7 7 9 Y
光源	LLD4000LCB1 ×1 845.0 l m
管理番号	K0182063 (0) DR 1
B Z 分類	BZ5 / 0.9 / BZ4 / 6.0 / BZ5 / 8.5 / BZ4

器具効率		59 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01) Z C M																				
保守率		良	0.63	0.6	34	27	22	19	33	27	22	19	32	26	22	19	31	25	22	19	18				
		中	0.6	0.8	40	33	29	25	39	33	28	25	37	32	28	25	36	31	28	25	24				
		否	0.56	1.0	44	38	33	30	43	37	33	30	41	36	32	30	40	35	32	29	28				
				1.25	47	42	38	34	46	41	37	34	45	40	37	34	43	39	36	34	32				
下方投影面積		c m ²	1.5	50	45	41	38	49	44	40	37	47	43	40	37	45	42	39	37	35					
等価発光面積			2.0	53	49	45	42	52	48	45	42	50	47	44	42	49	46	43	41	40					
			2.5	55	51	48	46	54	51	48	46	52	50	47	45	51	48	46	44	43					
取付高さ	器具間隔最大限		3.0	57	53	51	48	56	53	50	48	54	51	49	47	52	50	48	47	45					
H m	1.22 H m		4.0	58	56	54	52	57	55	53	51	56	54	52	51	54	53	51	50	48					
			5.0	59	57	56	54	59	57	55	53	57	55	54	53	55	54	53	52	50					
			7.0	61	59	58	56	60	58	57	56	58	57	56	55	57	56	55	54	52					
			10.0	62	61	60	59	61	60	59	58	59	59	58	57	58	57	57	56	54					

