

| 屋内照明器具特性 |                         |
|----------|-------------------------|
| 品番 (品名)  | XLGE5012                |
| 光源       | LLD4000VCE1 ×1 845.0 lm |
| 管理番号     | K0181592 ( 0 ) DR 1     |
| BZ分類     | BZ5                     |

| 器具効率         |                 | 83 %            | 反射率  | 天井                 | 80 % |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |  |
|--------------|-----------------|-----------------|------|--------------------|------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|--|
|              |                 |                 |      | 壁                  | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |  |
|              |                 |                 |      | 床                  | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |  |
| 上方光束<br>下方光束 |                 | 13 %<br>70 %    | 室指数  | 照明率 ( X0.01 ) Z CM |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |  |
| 保守率          |                 | 良<br>中<br>否     | 0.63 | 0.6                | 44   | 34 | 27 | 23 | 42   | 33 | 27 | 22 | 39   | 31 | 25 | 22 | 36   | 29 | 24 | 21 | 18  |  |
|              |                 |                 | 0.6  | 0.8                | 52   | 42 | 35 | 31 | 50   | 41 | 35 | 30 | 46   | 39 | 33 | 29 | 43   | 36 | 32 | 28 | 25  |  |
|              |                 |                 | 0.56 | 1.0                | 57   | 48 | 41 | 37 | 55   | 47 | 40 | 36 | 51   | 44 | 39 | 34 | 47   | 41 | 37 | 33 | 30  |  |
|              |                 |                 |      | 1.25               | 62   | 54 | 47 | 42 | 60   | 52 | 46 | 42 | 55   | 49 | 44 | 40 | 51   | 46 | 42 | 38 | 35  |  |
| 下方投影面積       |                 | cm <sup>2</sup> |      | 1.5                | 65   | 58 | 52 | 47 | 63   | 56 | 51 | 46 | 59   | 53 | 48 | 44 | 54   | 50 | 46 | 42 | 38  |  |
| 等価発光面積       |                 | cm <sup>2</sup> |      | 2.0                | 70   | 64 | 58 | 54 | 68   | 62 | 57 | 53 | 63   | 58 | 54 | 50 | 59   | 55 | 51 | 48 | 44  |  |
| 取付<br>高さ     | 器具間隔最大限         |                 |      | 2.5                | 73   | 67 | 63 | 59 | 71   | 65 | 61 | 57 | 66   | 62 | 58 | 55 | 61   | 58 | 55 | 52 | 48  |  |
|              | 横方向 (A) 縦方向 (B) |                 |      | 3.0                | 75   | 70 | 66 | 62 | 73   | 68 | 64 | 61 | 68   | 64 | 61 | 58 | 63   | 60 | 58 | 55 | 50  |  |
| H m          | 1.30 H m        | 1.30 H m        |      | 4.0                | 78   | 74 | 70 | 67 | 75   | 72 | 68 | 65 | 71   | 68 | 65 | 62 | 66   | 64 | 61 | 59 | 54  |  |
|              |                 |                 |      | 5.0                | 79   | 76 | 73 | 70 | 77   | 74 | 71 | 69 | 72   | 70 | 67 | 65 | 68   | 66 | 64 | 62 | 57  |  |
|              |                 |                 |      | 7.0                | 81   | 79 | 76 | 74 | 79   | 77 | 74 | 72 | 74   | 72 | 71 | 69 | 70   | 68 | 67 | 65 | 60  |  |
|              |                 |                 |      | 10.0               | 83   | 81 | 79 | 78 | 80   | 79 | 77 | 76 | 76   | 74 | 73 | 72 | 71   | 70 | 69 | 68 | 62  |  |

