

屋内照明器具特性	
品番 (品名)	XLGE5017
光源	LLD4000LCE1 ×1 845.0 lm
管理番号	K0181595 (0) DR 1
BZ分類	BZ5

器具効率		83 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.63	0.6	44	34	27	23	42	33	27	22	39	31	26	22	36	29	24	21	19
			0.6	0.8	52	42	36	31	50	41	35	30	46	39	33	29	43	37	32	28	25
			0.56	1.0	57	48	42	37	55	47	41	36	51	44	39	35	47	42	37	33	30
				1.25	62	54	48	43	60	52	46	42	56	49	44	40	52	46	42	39	35
下方投影面積 等価発光面積		cm ²		1.5	66	58	52	47	63	56	51	46	59	53	48	44	55	50	46	43	39
				2.0	70	64	58	54	68	62	57	53	63	58	54	51	59	55	52	49	44
				2.5	73	68	63	59	71	66	61	58	66	62	58	55	62	58	55	53	48
				3.0	75	70	66	62	73	68	64	61	68	64	61	58	64	61	58	56	51
H _m	1.30H _m	1.30H _m		4.0	78	74	70	67	76	72	69	66	71	68	65	63	66	64	62	60	55
				5.0	80	76	73	70	77	74	71	69	73	70	68	66	68	66	64	62	57
				7.0	82	79	77	74	79	77	75	73	75	73	71	69	70	69	67	66	60
				10.0	83	81	79	78	81	79	77	76	76	75	73	72	72	71	70	68	63

