

屋内照明器具特性	
品番 (品名)	XLGE5019
光源	LLD4000NCE1 ×1 845.0 lm
管理番号	K0181595 (0) DR1
BZ分類	BZ5

器具効率		83 % 上方光束 12 % 下方光束 71 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						室指数	照明率 (X0.01) ZCM															
保守率		良 中 否	0.63	0.6	44	34	27	23	42	33	27	22	39	31	26	22	36	29	24	21	19	
			0.6	0.8	52	42	36	31	50	41	35	30	46	39	33	29	43	37	32	28	25	
			0.56	1.0	57	48	42	37	55	47	41	36	51	44	39	35	47	42	37	33	30	
			1.25	62	54	48	43	60	52	46	42	56	49	44	40	52	46	42	39	35		
下方投影面積		cm ²	1.5	66	58	52	47	63	56	51	46	59	53	48	44	55	50	46	43	39		
			2.0	70	64	58	54	68	62	57	53	63	58	54	51	59	55	52	49	44		
取付 高さ	器具間隔最大限		2.5	73	68	63	59	71	66	61	58	66	62	58	55	62	58	55	53	48		
	横方向 (A)	縦方向 (B)	3.0	75	70	66	62	73	68	64	61	68	64	61	58	64	61	58	56	51		
H m	1.30 H m	1.30 H m	4.0	78	74	70	67	76	72	69	66	71	68	65	63	66	64	62	60	55		
			5.0	80	76	73	70	77	74	71	69	73	70	68	66	68	66	64	62	57		
			7.0	82	79	77	74	79	77	75	73	75	73	71	69	70	69	67	66	60		
			10.0	83	81	79	78	81	79	77	76	76	75	73	72	72	71	70	68	63		

