

屋内照明器具特性	
品番 (品名)	XLGE5102
光源	LLD2000VCE1 ×1 531.0 lm
管理番号	K0181597 (0) DR1
BZ分類	BZ5/0.7/BZ4

器具効率		72 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
				室指数	照明率 (X0.01)																	Z	CM
保守率		良 中 否	0.63	0.6	41	33	27	23	40	32	27	23	39	31	27	23	37	31	26	23	22		
			0.6	0.8	48	40	35	31	47	40	35	31	45	39	34	31	44	38	34	30	29		
			0.56	1.0	53	46	40	36	52	45	40	36	50	44	39	36	48	43	39	36	34		
			1.25	57	51	46	42	56	50	45	41	54	49	45	41	52	48	44	41	39			
下方投影面積		cm ²	1.5	60	54	49	46	59	54	49	45	57	52	48	45	55	51	47	45	43			
			2.0	64	59	55	52	63	58	55	51	61	57	54	51	59	56	53	50	48			
等価発光面積		cm ²	2.5	67	62	59	56	66	62	58	55	64	60	57	55	62	59	56	54	52			
			3.0	68	65	61	59	67	64	61	58	65	62	60	57	63	61	59	57	55			
H	m	1.22 H	m	1.22 H	m	4.0	71	68	65	63	70	67	64	62	68	65	63	61	66	64	62	60	58
					5.0	72	70	67	65	71	69	67	65	69	67	65	64	67	66	64	63	61	
					7.0	73	72	70	68	73	71	69	68	71	69	68	67	69	68	67	66	64	
					10.0	75	73	72	71	74	72	71	70	72	71	70	69	70	69	69	68	66	

