

屋内照明器具特性	
品番 (品名)	XLGE5104
光源	LLD2000LCE1 ×1 531.0 lm
管理番号	K0181598 (0) DR1
BZ分類	BZ5/0.9/BZ4/6.0/BZ5/8.5/BZ4

器具効率		66 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
				室指数	照明率 (X0.01)																Z	CM	
保守率		良 中 否	0.63	0.6	38	30	25	21	37	30	25	21	35	29	24	21	34	28	24	21	20		
			0.6	0.8	44	37	32	28	44	37	32	28	42	36	31	28	40	35	31	28	27		
			0.56	1.0	49	42	37	33	48	41	37	33	46	40	36	33	44	39	36	33	31		
				1.25	53	47	42	38	52	46	41	38	50	45	41	38	48	44	40	37	36		
下方投影面積 等価発光面積		cm ²		1.5	55	50	45	42	54	49	45	42	52	48	44	41	51	47	44	41	39		
				2.0	59	54	51	47	58	54	50	47	56	52	49	47	54	51	48	46	44		
				2.5	61	57	54	51	60	57	53	51	58	55	52	50	57	54	52	49	48		
				3.0	63	59	56	54	62	59	56	53	60	57	55	53	58	56	54	52	50		
H	m	1.22 H	m	1.22 H	m	4.0	65	62	60	58	64	61	59	57	62	60	58	56	60	59	57	55	54
				5.0	66	64	62	60	65	63	61	59	63	62	60	59	62	60	59	58	56		
				7.0	68	66	64	63	67	65	64	62	65	64	62	61	63	62	61	60	58		
				10.0	69	67	66	65	68	67	66	65	66	65	64	63	65	64	63	62	60		

