

屋内照明器具特性	
品番 (品名)	XLGE5109
光源	LLD2000NCE1 ×1 531.0 lm
管理番号	K0181600 (0) DR1
BZ分類	BZ5/0.9/BZ4/6.0/BZ5/8.5/BZ4

器具効率		70 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
上方光束		0 %	室指数	照明率 (X0.01)																		Z	CM
下方光束		70 %																					
保守率		良 中 否	0.63	0.6	40	32	26	23	39	31	26	23	38	31	26	22	36	30	26	22	21		
			0.6	0.8	47	39	34	30	46	39	34	30	44	38	33	30	42	37	33	30	28		
				1.0	52	44	39	35	51	44	39	35	49	43	38	35	47	42	38	35	33		
			0.56	1.25	56	49	44	40	55	49	44	40	53	47	43	40	51	46	43	40	38		
下方投影面積		cm ²		1.5	59	53	48	44	58	52	48	44	55	51	47	44	53	49	46	43	42		
				2.0	63	58	53	50	61	57	53	50	59	55	52	49	57	54	51	49	47		
等価発光面積		cm ²		2.5	65	61	57	54	64	60	57	54	62	58	56	53	60	57	55	52	51		
				3.0	67	63	60	57	66	62	59	57	64	61	58	56	62	59	57	55	53		
H	m	1.22 H	m	1.22 H	m	4.0	69	66	63	61	68	65	63	60	66	63	61	60	64	62	60	59	57
						5.0	70	68	65	63	69	67	65	63	67	65	64	62	65	64	62	61	59
						7.0	72	70	68	67	71	69	67	66	69	67	66	65	67	66	65	64	62
						10.0	73	71	70	69	72	71	69	68	70	69	68	67	68	67	67	66	64

