

屋内照明器具特性	
品番 (品名)	XLGE5113
光源	LLD4000NCE1 ×1 845.0 lm
管理番号	K0181604 (0) DR 1
BZ分類	BZ5/1.1/BZ4/6.0/BZ5/8.5/BZ4

器具効率		69 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.63	0.6	39	31	26	22	39	31	26	22	37	30	25	22	35	29	25	22	21
			0.6	0.8	46	39	33	29	45	38	33	29	43	37	33	29	42	36	32	29	28
			0.56	1.0	51	44	38	35	50	43	38	34	48	42	38	34	46	41	37	34	33
				1.25	55	48	44	40	54	48	43	40	52	47	43	39	50	45	42	39	37
下方投影面積 等価発光面積		cm ²		1.5	58	52	47	44	57	51	47	43	55	50	46	43	53	49	45	43	41
				2.0	62	57	53	49	60	56	52	49	58	55	51	48	56	53	50	48	46
				2.5	64	60	56	53	63	59	56	53	61	58	55	52	59	56	54	52	50
				3.0	66	62	59	56	65	61	58	56	63	60	57	55	61	58	56	54	52
H _m	1.23H _m	1.23H _m		4.0	68	65	62	60	67	64	62	60	65	63	60	59	63	61	59	58	
				5.0	69	67	64	62	68	66	64	62	66	64	63	61	64	63	61	60	
				7.0	70	69	67	66	70	68	66	65	68	66	65	64	66	65	64	63	
				10.0	72	70	69	68	71	69	68	67	69	68	67	66	67	66	66	65	

