

屋内照明器具特性	
品番 (品名)	LGBZ6190
光源	LED4000_70_3500 ×1 3500.0 lm
管理番号	K0179196 (0) DB 1
BZ分類	BZ5 / 0.7 / BZ4

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %						
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %						
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %						
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																			Z C M				
下方光束				1 0 0 %																							
保守率		良 中 否	0 . 6 7	0 . 6	5 8	4 6	3 9	3 4	5 7	4 6	3 9	3 3	5 5	4 5	3 8	3 3	5 2	4 4	3 8	3 3	3 1						
			0 . 6 3	0 . 8	6 9	5 8	5 0	4 5	6 7	5 7	5 0	4 4	6 4	5 5	4 9	4 4	6 2	5 4	4 8	4 4	4 2						
			0 . 5 6	1 . 0	7 5	6 5	5 8	5 2	7 4	6 4	5 8	5 2	7 1	6 3	5 7	5 2	6 8	6 1	5 6	5 2	4 9						
				1 . 2 5	8 1	7 2	6 6	6 0	8 0	7 1	6 5	6 0	7 7	7 0	6 4	5 9	7 4	6 8	6 3	5 9	5 7						
下方投影面積		c m ²	1 . 5	8 6	7 7	7 1	6 6	8 4	7 6	7 0	6 6	8 1	7 4	6 9	6 5	7 8	7 3	6 8	6 4	6 2							
等価発光面積			c m ²	2 . 0	9 1	8 4	7 9	7 4	8 9	8 3	7 8	7 4	8 6	8 1	7 7	7 3	8 4	7 9	7 5	7 2	7 0						
				2 . 5	9 4	8 9	8 4	8 0	9 3	8 8	8 3	7 9	9 0	8 6	8 2	7 8	8 7	8 4	8 0	7 7	7 5						
取付 高さ	器具間隔最大限		2 . 5	9 4	8 9	8 4	8 0	9 3	8 8	8 3	7 9	9 0	8 6	8 2	7 8	8 7	8 4	8 0	7 7	7 5							
	横方向 (A)		縦方向 (B)		3 . 0	9 7	9 2	8 8	8 4	9 5	9 1	8 7	8 3	9 2	8 9	8 5	8 2	9 0	8 6	8 4	8 1	7 9					
H m	1 . 2 6 H m		1 . 2 6 H m		4 . 0	1 0 0	9 6	9 2	8 9	9 8	9 5	9 2	8 9	9 5	9 2	9 0	8 7	9 3	9 0	8 8	8 6	8 3					
					5 . 0	1 0 1	9 8	9 5	9 3	1 0 0	9 7	9 4	9 2	9 7	9 5	9 3	9 1	9 5	9 3	9 1	8 9	8 6					
					7 . 0	1 0 3	1 0 1	9 9	9 7	1 0 2	1 0 0	9 8	9 6	9 9	9 8	9 6	9 4	9 7	9 5	9 4	9 3	9 0					
					1 0 . 0	1 0 5	1 0 3	1 0 2	1 0 0	1 0 3	1 0 2	1 0 1	9 9	1 0 1	1 0 0	9 8	9 7	9 9	9 7	9 6	9 5	9 3					

