

屋内照明器具特性

品番 (品名)	LGBZ1615															
光源	LED6200_70_4100 x1 4100.0 lm															
管理番号	K0161881(1)D 1															
BZ分類	BZ6/0.7/BZ5															

器具効率	100%	天井	80%				70%				50%				30%				0%			
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
				床	10%				10%				10%				10%				0%	
上方光束	3%	室指数																				
下方光束	97%	照明率 (X0.01) ZCM																				
保守率	良 中 否	0.63	0.6	0.56	0.6	54	41	33	27	52	40	32	27	49	39	32	27	47	38	31	26	24
		0.6	0.8	64	52	43	37	62	51	43	37	59	49	42	36	56	47	41	36	34		
		0.56	1.0	70	59	51	44	69	58	50	44	65	56	49	44	62	54	48	43	40		
			1.25	76	66	58	52	75	65	57	52	71	63	56	51	68	60	55	50	47		
下方投影面積	c m ²	1.5	81	71	64	58	79	70	63	57	75	67	61	56	72	65	60	55	52			
		2.0	87	78	72	66	85	77	71	66	81	74	69	64	77	72	67	63	60			
取付高さ	器具間隔最大限		2.5	90	83	77	72	88	82	76	71	85	79	74	70	81	76	72	69	66		
	横方向 (A)	縦方向 (B)	3.0	93	87	81	76	91	85	80	76	87	82	78	74	84	80	76	73	70		
H m	1.42 H m	1.42 H m	4.0	96	91	87	83	94	90	85	82	91	87	83	80	87	84	81	78	75		
			5.0	98	94	90	87	96	93	89	86	93	90	87	84	90	87	84	82	78		
			7.0	101	98	94	92	99	96	93	91	96	93	91	89	92	90	88	86	83		
			10.0	103	100	98	96	101	99	97	95	98	96	94	92	95	93	92	90	86		

