

屋内照明器具特性	
品番 (品名)	XAD3 1 2 0 L K
光源	L L D 3 0 2 0 L C B 1 × 1 7 9 5 . 0 l m
管理番号	K 0 1 7 5 5 2 9 (2) D R 1
B Z 分類	B Z 1

器具効率		88 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																			Z C M	
下方光束		88 %																						
保守率		良	0 . 6 7	0 . 6	73	67	64	61	72	67	64	61	71	67	63	61	70	66	63	61	60			
		中	0 . 6 3	0 . 8	78	73	70	68	78	73	70	67	76	72	69	67	75	71	69	67	66			
		否	0 . 5 6	1 . 0	82	77	74	72	81	77	74	71	79	76	73	71	78	75	73	71	70			
				1 . 2 5	84	80	78	75	84	80	77	75	82	79	76	75	80	78	76	74	73			
下方投影面積		c m ²		1 . 5	86	83	80	78	85	82	80	78	84	81	79	77	82	80	78	76	75			
等価発光面積		c m ²		2 . 0	89	86	83	81	88	85	83	81	86	84	82	80	84	82	81	80	78			
取付 高さ	器具間隔最大限			2 . 5	90	88	86	84	89	87	85	83	87	85	84	82	86	84	83	82	80			
	横方向 (A)		縦方向 (B)	3 . 0	91	89	87	85	90	88	86	85	88	86	85	84	86	85	84	83	81			
H m	0 . 4 1 H m	0 . 4 1 H m	4 . 0	92	90	89	88	91	90	88	87	89	88	87	86	87	86	86	85	83				
			5 . 0	93	91	90	89	92	90	89	88	90	89	88	87	88	87	86	86	84				
			7 . 0	93	92	92	91	92	92	91	90	90	90	89	88	89	88	88	87	85				
			10 . 0	94	93	93	92	93	92	92	91	91	91	90	89	89	88	88	88	86				

