

# 屋内照明器具特性

品番 (品名)	LGB14521	
光源	LED6200_70_4578 x1 4578.0 lm	
管理番号	K0161788(0)D 1	
BZ分類	BZ5	

器具効率	100%	天井	80%				70%				50%				30%				0%				
	上方光束 7%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
下方光束	93%	床	10%				10%				10%				10%				0%				
室指数			照明率 ( X0.01 )																				ZCM
保守率	良 0.67	0.6	56	44	36	31	54	43	35	30	51	41	35	30	48	40	34	29	27				
	中 0.63	0.8	66	54	46	41	64	53	46	40	60	51	44	40	57	49	43	39	36				
	否 0.56	1.0	72	61	54	48	70	60	53	48	66	58	52	47	63	56	50	46	43				
		1.25	78	68	61	55	76	67	60	55	72	64	58	54	68	62	57	53	49				
下方投影面積	cm <sup>2</sup>	1.5	82	73	67	61	80	72	66	60	76	69	64	59	72	66	62	58	54				
等価発光面積	cm <sup>2</sup>	2.0	88	81	74	69	86	79	73	69	81	76	71	67	78	73	69	65	62				
取付高さ	器具間隔最大限		2.5	91	85	80	75	89	83	79	74	85	80	76	72	81	77	74	70				
	横方向 (A)	縦方向 (B)	3.0	94	88	84	80	92	87	82	78	88	83	80	76	84	80	77	74				
Hm	1.24Hm	1.24Hm	4.0	97	93	89	85	95	91	87	84	91	87	84	82	87	84	82	79				
			5.0	99	95	92	89	97	93	90	88	93	90	87	85	89	87	85	83				
			7.0	101	98	96	94	99	97	94	92	95	93	91	89	91	90	88	87				
			10.0	103	101	99	97	101	99	97	96	97	95	94	93	93	92	91	90				

