

屋内照明器具特性	
品番 (品名)	XAD1101VK
光源	LLD2000VCE1 ×1 531.0 lm
管理番号	K0175548 (0) DR1
BZ分類	BZ4/0.7/BZ3

器具効率		6 4 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1)																
保守率		良 中 否	0 . 6 7	0 . 6	3 9	3 2	2 7	2 4	3 8	3 1	2 7	2 4	3 7	3 1	2 7	2 4	3 5	3 0	2 6	2 4	2 3
			0 . 6 3	0 . 8	4 6	3 9	3 5	3 1	4 5	3 9	3 4	3 1	4 3	3 8	3 4	3 1	4 2	3 7	3 4	3 1	3 0
			0 . 5 6	1 . 0	5 0	4 4	4 0	3 7	4 9	4 4	4 0	3 7	4 7	4 3	3 9	3 6	4 6	4 2	3 9	3 6	3 5
				1 . 2 5	5 4	4 9	4 5	4 2	5 3	4 8	4 4	4 1	5 1	4 7	4 4	4 1	5 0	4 6	4 3	4 1	3 9
下方投影面積		c m ²	1 . 5	5 6	5 2	4 8	4 5	5 5	5 1	4 8	4 5	5 4	5 0	4 7	4 4	5 2	4 9	4 6	4 4	4 3	
			等価発光面積	2 . 0	5 9	5 6	5 2	5 0	5 9	5 5	5 2	5 0	5 7	5 4	5 1	4 9	5 5	5 3	5 0	4 9	4 7
取付高さ	器具間隔最大限		2 . 5	6 1	5 8	5 5	5 3	6 0	5 8	5 5	5 3	5 9	5 6	5 4	5 2	5 7	5 5	5 3	5 2	5 0	
	横方向 (A)		縦方向 (B)	3 . 0	6 3	6 0	5 8	5 5	6 2	5 9	5 7	5 5	6 0	5 8	5 6	5 4	5 9	5 7	5 5	5 4	5 2
H m	1 . 2 5 H m		1 . 2 5 H m	4 . 0	6 4	6 2	6 0	5 8	6 3	6 1	6 0	5 8	6 2	6 0	5 9	5 7	6 0	5 9	5 8	5 6	5 5
				5 . 0	6 5	6 4	6 2	6 0	6 4	6 3	6 1	6 0	6 3	6 1	6 0	5 9	6 1	6 0	5 9	5 8	5 6
				7 . 0	6 6	6 5	6 4	6 3	6 6	6 4	6 3	6 2	6 4	6 3	6 2	6 1	6 3	6 2	6 1	6 0	5 8
				1 0 . 0	6 7	6 6	6 5	6 5	6 6	6 6	6 5	6 4	6 5	6 4	6 4	6 3	6 3	6 3	6 2	6 2	6 0

