

屋内照明器具特性	
品番 (品名)	XAD3 1 3 1 VK
光源	LLD3020MVCE1 ×1 795.0 lm
管理番号	K0175526 (0) DR 1
BZ分類	BZ1

器具効率		68 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
上方光束		0 %	室指数	照明率 (X0.01)																			
下方光束		68 %		ZCM																			
保守率		良	0.67	0.6	56	52	49	47	56	52	49	47	55	51	49	47	54	51	49	47	46		
		中	0.63	0.8	60	56	54	52	60	56	54	52	59	56	53	52	58	55	53	52	51		
		否	0.56	1.0	63	59	57	55	62	59	57	55	61	58	56	55	60	58	56	54	54		
				1.25	65	62	60	58	64	62	59	58	63	61	59	57	62	60	58	57	56		
下方投影面積		c m ²	1.5	66	64	62	60	66	63	61	60	64	62	61	59	63	62	60	59	58			
等価発光面積			c m ²	2.0	68	66	64	63	67	65	64	62	66	64	63	62	65	64	62	61	60		
取付	器具間隔最大限		2.5	69	67	66	65	69	67	65	64	67	66	65	64	66	65	64	63	62			
高さ	横方向 (A)		縦方向 (B)	3.0	70	68	67	66	69	68	67	65	68	67	66	65	67	66	65	64	62		
H m	0.41 H m			0.41 H m	4.0	71	70	69	68	70	69	68	67	69	68	67	66	67	67	66	64		
			5.0	71	70	69	69	71	70	69	68	69	68	68	67	68	67	67	66	64			
			7.0	72	71	71	70	71	71	70	69	70	69	69	68	68	68	67	67	65			
			10.0	72	72	71	71	72	71	71	70	70	70	69	69	69	68	68	68	66			

