

屋内照明器具特性	
品番 (品名)	XAD3 1 0 2 VK
光源	LLD4000VCE1 ×1 845.0 lm
管理番号	K0175542 (0) DR 1
BZ分類	BZ3

器具効率		64 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z
保守率		良 中 否	0.67	0.6	41	35	30	27	40	34	30	27	39	34	30	27	38	33	30	27	26
			0.63	0.8	47	41	37	34	47	41	37	34	45	40	37	34	44	39	36	34	33
			0.56	1.0	51	46	42	39	50	45	42	39	49	44	41	38	47	44	41	38	37
				1.25	55	50	46	43	54	49	46	43	52	48	45	43	51	47	45	42	41
下方投影面積		cm ²		1.5	57	52	49	46	56	52	49	46	54	51	48	46	53	50	47	45	44
				2.0	60	56	53	51	59	55	53	50	57	54	52	50	56	53	51	49	48
等価発光面積		cm ²		2.5	62	58	56	53	61	58	55	53	59	56	54	53	57	55	53	52	50
				3.0	63	60	58	56	62	59	57	55	60	58	56	54	59	57	55	54	52
H	m	1.18 H	m	1.18 H	m	4.0	64	62	60	58	63	61	60	58	62	60	59	57	56	55	
						5.0	65	63	62	60	64	63	61	60	63	61	60	59	58	56	
						7.0	66	65	64	62	65	64	63	62	64	63	62	61	60	58	
						10.0	67	66	65	64	66	65	64	64	65	64	63	62	61	59	

