

屋内照明器具特性	
品番 (品名)	XAD3 1 2 2 VK
光源	L L D 3 0 2 0 V C E 1 × 1 7 9 5 . 0 l m
管理番号	K 0 1 7 5 5 4 4 (0) D R 1
B Z 分類	B Z 1

器具効率		6 8 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		6 8 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束																						
保守率		良 中 否	0 . 6	5 7	5 2	5 0	4 8	5 6	5 2	5 0	4 8	5 5	5 2	4 9	4 8	5 4	5 1	4 9	4 8	4 7		
			0 . 8	6 1	5 7	5 4	5 3	6 0	5 7	5 4	5 2	5 9	5 6	5 4	5 2	5 8	5 6	5 4	5 2	5 1		
			1 . 0	6 3	6 0	5 7	5 6	6 3	5 9	5 7	5 5	6 1	5 9	5 7	5 5	6 0	5 8	5 6	5 5	5 4		
			0 . 5 6	1 . 2 5	6 5	6 2	6 0	5 8	6 5	6 2	6 0	5 8	6 3	6 1	5 9	5 8	6 2	6 0	5 9	5 7	5 6	
下方投影面積		c m ²	1 . 5	6 7	6 4	6 2	6 0	6 6	6 3	6 2	6 0	6 5	6 3	6 1	6 0	6 3	6 2	6 0	5 9	5 8		
			等価発光面積		c m ²	2 . 0	6 8	6 6	6 4	6 3	6 8	6 6	6 4	6 3	6 6	6 5	6 3	6 2	6 5	6 4	6 2	6 1
取付 高さ	器具間隔最大限		2 . 5	6 9	6 8	6 6	6 5	6 9	6 7	6 6	6 4	6 7	6 6	6 5	6 4	6 6	6 5	6 4	6 3	6 2		
	横方向 (A) 縦方向 (B)		3 . 0	7 0	6 8	6 7	6 6	6 9	6 8	6 7	6 6	6 8	6 7	6 6	6 5	6 7	6 6	6 5	6 4	6 3		
H m	0 . 4 1 H m	0 . 4 1 H m	4 . 0	7 1	7 0	6 9	6 8	7 0	6 9	6 8	6 7	6 9	6 8	6 7	6 6	6 7	6 7	6 6	6 5	6 4		
			5 . 0	7 1	7 0	6 9	6 9	7 1	7 0	6 9	6 8	6 9	6 8	6 8	6 7	6 8	6 7	6 7	6 6	6 5		
			7 . 0	7 2	7 1	7 1	7 0	7 1	7 1	7 0	6 9	7 0	6 9	6 9	6 8	6 8	6 8	6 7	6 7	6 5		
			1 0 . 0	7 2	7 2	7 1	7 1	7 2	7 1	7 1	7 0	7 0	7 0	6 9	6 9	6 9	6 8	6 8	6 8	6 6		

