

屋内照明器具特性	
品番 (品名)	XAD3101K
光源	LLD3000CU1 ×1 795.0 lm
管理番号	K0178936 (0) DR 1
BZ分類	BZ4/0.7/BZ3

器具効率		68 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z CM
保守率		良 中 否	0.67	0.6	42	34	29	26	41	34	29	26	39	33	29	26	38	32	29	26	24
			0.63	0.8	49	42	37	34	48	42	37	34	46	41	37	34	45	40	36	33	32
			0.56	1.0	53	47	43	39	53	47	43	39	51	46	42	39	49	45	42	39	38
				1.25	57	52	48	45	56	51	48	45	55	50	47	44	53	49	46	44	43
下方投影面積		cm ²		1.5	60	55	51	48	59	55	51	48	57	53	50	48	56	52	50	47	46
			等価発光面積	cm ²	2.0	64	60	56	54	63	59	56	53	61	58	55	53	59	57	54	52
取付 高さ	器具間隔最大限			2.5	66	62	60	57	65	62	59	57	63	60	58	56	61	59	57	56	54
	横方向 (A)		縦方向 (B)	3.0	67	64	62	60	66	63	61	59	64	62	60	58	63	61	59	58	56
H m	1.23 H m		1.23 H m	4.0	69	66	64	63	68	66	64	62	66	64	63	61	64	63	62	61	59
				5.0	70	68	66	65	69	67	66	64	67	66	64	63	65	64	63	62	61
				7.0	71	69	68	67	70	69	68	67	68	67	66	65	67	66	65	64	62
				10.0	72	71	70	69	71	70	69	68	69	68	68	67	68	67	66	66	64

