

屋内照明器具特性	
品番 (品名)	L G B 1 6 8 0 3
光源	LDG3 L / F 8 / C / B 2 × 1 3 0 0 . 0 l m
管理番号	K 0 1 7 8 6 5 4 (0) D B 1
B Z 分類	B Z 7

器具効率		7 1 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
上方光束		5 %	室指数	照明率 (X 0 . 0 1)																	Z C M
下方光束		6 6 %																			
保守率		良 中 否	0 . 6 7	0 . 6	3 5	2 5	1 9	1 4	3 3	2 4	1 8	1 4	3 1	2 3	1 8	1 4	2 9	2 2	1 7	1 3	1 1
			0 . 6 3	0 . 8	4 1	3 1	2 5	2 0	4 0	3 1	2 4	2 0	3 7	2 9	2 3	1 9	3 4	2 7	2 2	1 9	1 7
			0 . 5 6	1 . 0	4 6	3 6	3 0	2 5	4 4	3 5	2 9	2 4	4 1	3 4	2 8	2 4	3 8	3 2	2 7	2 3	2 1
				1 . 2 5	5 0	4 1	3 5	3 0	4 8	4 0	3 4	2 9	4 5	3 8	3 3	2 8	4 2	3 6	3 1	2 8	2 5
下方投影面積		c m ²	1 . 5	5 3	4 5	3 9	3 4	5 1	4 4	3 8	3 3	4 8	4 2	3 6	3 2	4 5	3 9	3 5	3 1	2 8	
等価発光面積			c m ²	2 . 0	5 8	5 0	4 5	4 0	5 6	4 9	4 4	3 9	5 2	4 7	4 2	3 8	4 9	4 4	4 0	3 7	3 4
取付 高さ	器具間隔最大限		2 . 5	6 0	5 4	4 9	4 4	5 8	5 3	4 8	4 4	5 5	5 0	4 6	4 2	5 2	4 8	4 4	4 1	3 8	
	横方向 (A) 縦方向 (B)		3 . 0	6 2	5 7	5 2	4 8	6 0	5 5	5 1	4 7	5 7	5 3	4 9	4 5	5 4	5 0	4 7	4 4	4 1	
H m	0 . 7 3 H m 0 . 7 3 H m		4 . 0	6 5	6 0	5 6	5 2	6 3	5 9	5 5	5 2	6 0	5 6	5 3	5 0	5 6	5 3	5 1	4 8	4 5	
			5 . 0	6 7	6 3	5 9	5 6	6 5	6 1	5 8	5 5	6 2	5 8	5 5	5 3	5 8	5 6	5 3	5 1	4 7	
			7 . 0	6 9	6 6	6 3	6 0	6 7	6 4	6 1	5 9	6 4	6 1	5 9	5 7	6 1	5 9	5 7	5 5	5 1	
			1 0 . 0	7 1	6 8	6 6	6 4	6 9	6 7	6 4	6 2	6 6	6 4	6 2	6 0	6 3	6 1	5 9	5 8	5 4	

