

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | S F 0 6 2 B                  |
| 光源       | LED2700_70_1960 ×1 1960.0 lm |
| 管理番号     | K0148410 ( 0 ) DB 1          |
| B Z 分類   | B Z 5                        |

| 器具効率     |           | 100 %           | 反射率    | 天井              | 80 %               |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|----------|-----------|-----------------|--------|-----------------|--------------------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|
|          |           |                 |        | 壁               | 70                 | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|          |           |                 |        | 床               | 10 %               |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|          |           |                 |        | 室指数             | 照明率 ( X0.01 ) Z CM |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |
| 保守率      |           | 良<br>中<br>否     | 0.67   | 0.6             | 55                 | 43 | 35 | 30 | 53   | 42 | 35 | 29 | 50   | 40 | 34 | 29 | 47   | 38 | 32 | 28 | 26  |
|          |           |                 | 0.63   | 0.8             | 65                 | 53 | 45 | 40 | 63   | 52 | 45 | 39 | 59   | 50 | 43 | 38 | 55   | 47 | 42 | 37 | 34  |
|          |           |                 | 0.56   | 1.0             | 71                 | 60 | 52 | 47 | 69   | 59 | 52 | 46 | 65   | 56 | 50 | 45 | 61   | 54 | 48 | 44 | 40  |
|          |           |                 |        | 1.25            | 77                 | 67 | 60 | 54 | 74   | 65 | 58 | 53 | 70   | 62 | 56 | 52 | 66   | 59 | 54 | 50 | 46  |
| 下方投影面積   |           | cm <sup>2</sup> |        | 1.5             | 81                 | 72 | 65 | 59 | 78   | 70 | 63 | 58 | 74   | 67 | 61 | 57 | 70   | 64 | 59 | 55 | 51  |
|          |           |                 | 等価発光面積 | cm <sup>2</sup> | 2.0                | 86 | 79 | 72 | 67   | 84 | 77 | 71 | 66   | 79 | 73 | 68 | 64   | 75 | 70 | 66 | 62  |
| 取付<br>高さ | 器具間隔最大限   |                 |        | 2.5             | 90                 | 83 | 77 | 73 | 87   | 81 | 76 | 71 | 82   | 77 | 73 | 69 | 78   | 74 | 70 | 67 | 62  |
|          | 横方向 ( A ) | 縦方向 ( B )       |        | 3.0             | 92                 | 86 | 81 | 77 | 90   | 84 | 80 | 75 | 85   | 80 | 76 | 73 | 80   | 77 | 73 | 70 | 66  |
| 1.5m     | 1.9 m     | 2.14 m          |        | 4.0             | 95                 | 90 | 86 | 82 | 93   | 88 | 84 | 81 | 88   | 84 | 81 | 78 | 84   | 81 | 78 | 75 | 70  |
| 2        | 2.51      | 2.71            |        | 5.0             | 97                 | 93 | 89 | 86 | 95   | 91 | 88 | 85 | 90   | 87 | 84 | 81 | 86   | 83 | 81 | 79 | 73  |
| 2.5      | 3.13      | 3.29            |        | 7.0             | 100                | 96 | 94 | 91 | 97   | 94 | 92 | 89 | 92   | 90 | 88 | 86 | 88   | 86 | 84 | 83 | 77  |
| 3        | 3.73      | 3.89            |        | 10.0            | 101                | 99 | 97 | 95 | 99   | 97 | 95 | 93 | 94   | 93 | 91 | 89 | 90   | 89 | 87 | 86 | 80  |

