

屋内照明器具特性	
品番 (品名)	L G B 1 5 1 2 6 K
光源	LDA4 L - G / S / K4 ×1 485.0 l m
管理番号	K0123308 (1) DB 1
B Z 分類	BZ3 / 0.9 / BZ4 / 3.5 / BZ5

器具効率		83 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.67	0.6	49	40	34	30	48	39	34	30	44	37	33	29	42	36	31	28	26
			0.63	0.8	57	48	42	38	55	47	42	38	51	45	40	37	48	43	39	35	33
			1.0	62	54	48	44	59	52	47	43	56	50	45	42	52	47	43	40	37	
			0.56	1.25	66	58	53	49	64	57	52	48	59	54	50	46	56	51	48	45	41
下方投影面積		cm ²	1.5	69	62	57	53	66	60	56	52	62	57	53	50	58	54	51	48	44	
			2.0	73	67	62	58	70	65	61	57	66	61	58	55	62	58	55	53	48	
等価発光面積		cm ²	2.5	75	70	66	62	73	68	64	61	68	64	61	58	64	61	58	56	51	
			3.0	77	72	69	65	74	70	67	64	70	66	64	61	65	63	60	58	54	
H _m	1.31 H _m	1.32 H _m	4.0	79	75	72	69	77	73	70	68	72	69	67	65	68	65	63	62	57	
			5.0	80	77	75	72	78	75	73	70	73	71	69	67	69	67	65	64	59	
			7.0	82	80	78	76	80	78	76	74	75	73	72	70	71	69	68	67	61	
			10.0	83	82	80	78	81	79	78	76	76	75	74	73	72	71	70	69	63	

