

屋内照明器具特性	
品番 (品名)	LGB57314Z
光源	LDA4L-H/S/4×3 485.0lm
管理番号	K0178890(0)DB1
BZ分類	BZ5/0.7/BZ4/1.1/BZ5

器具効率		91 %	反射率	天井	80 %				70 %				50 %				30 %				0 %					
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %					
				床	10 %				10 %				10 %				10 %				0 %					
上方光束		19 %	室指数	照明率 (X0.01)																			Z	C		M
下方光束		72 %																								
保守率		良 中 否	0.67	0.6	50	39	33	28	48	38	32	27	44	36	30	26	40	33	29	25	22					
			0.63	0.8	58	49	42	37	56	47	41	36	51	44	39	34	47	41	36	33	29					
			1.0	64	55	48	43	61	53	47	42	57	50	44	40	52	46	42	38	34						
			0.56	1.25	69	61	54	49	66	59	53	48	61	55	50	46	56	51	47	44	39					
下方投影面積		cm ²	1.5	73	65	59	54	70	63	57	53	64	59	54	50	59	55	51	48	43						
等価発光面積			cm ²	2.0	77	71	65	61	74	68	64	59	69	64	60	56	63	59	56	53	48					
取付 高さ	器具間隔最大限		2.5	80	75	70	66	77	72	68	64	71	67	64	61	66	63	60	57	51						
	横方向 (A)		縦方向 (B)		3.0	82	77	73	69	79	75	71	67	73	70	66	64	68	65	62	60	54				
H m	1.24 H m		1.26 H m		4.0	85	81	77	74	82	78	75	72	76	73	70	68	70	68	66	64	57				
					5.0	87	83	80	77	84	80	78	75	78	75	73	71	72	70	68	66	60				
					7.0	89	86	84	81	85	83	81	79	79	78	76	74	74	72	71	69	62				
					10.0	90	88	86	85	87	85	84	82	81	80	78	77	75	74	73	72	65				

