

屋内照明器具特性	
品番 (品名)	L G B 8 1 6 4 5 Z
光源	LDA7L - H/ S/ 6 ×1 810.0 lm
管理番号	K0179178 (0) DB 1
B Z 分類	BZ5/ 0.7/ BZ4/ 1.8/ BZ5

器具効率		93 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束 下方光束		19 % 74 %	室指数	照明率 (X0.01) Z C M																		
保守率		良 中 否	0.67	0.6	51	41	34	29	49	39	33	28	45	37	31	27	42	34	30	26	23	
			0.63	0.8	60	50	43	38	58	49	42	37	53	46	40	36	49	43	38	34	31	
			1.0	66	57	50	45	64	55	49	44	59	51	46	42	54	48	44	40	36		
			0.56	1.25	72	63	57	52	69	61	55	50	63	57	52	48	58	53	49	46	41	
下方投影面積		cm ²	1.5	75	67	61	56	72	65	59	55	67	61	56	52	61	57	53	50	45		
等価発光面積		cm ²	2.0	80	73	68	63	77	71	66	62	71	66	62	59	66	62	58	55	50		
取付 高さ	器具間隔最大限		2.5	83	77	72	68	80	75	70	66	74	70	66	63	68	65	62	59	53		
	横方向 (A) 縦方向 (B)		3.0	85	80	76	72	82	77	73	70	76	72	69	66	70	67	65	62	56		
H m	1.36 H m	1.41 H m	4.0	88	84	80	77	84	81	77	75	78	75	73	70	73	70	68	66	59		
			5.0	89	86	83	80	86	83	80	78	80	77	75	73	74	72	70	69	62		
			7.0	91	89	86	84	88	86	83	81	82	80	78	77	76	75	73	72	65		
			10.0	93	91	89	87	90	88	86	85	83	82	81	79	78	77	75	74	67		

