

屋内照明器具特性	
品番 (品名)	LGB58027K
光源	LDA4L-G/S/K4 ×1 485.0 lm
管理番号	K0123308 (1) DB1
BZ分類	BZ3/0.9/BZ4/3.5/BZ5

器具効率		83 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		13 %	室指数	照明率 (X0.01)																			Z	CM
下方光束		70 %																						
保守率		良 中 否	0.67	0.6	49	40	34	30	48	39	34	30	44	37	33	29	42	36	31	28	26			
			0.63	0.8	57	48	42	38	55	47	42	38	51	45	40	37	48	43	39	35	33			
			0.56	1.0	62	54	48	44	59	52	47	43	56	50	45	42	52	47	43	40	37			
				1.25	66	58	53	49	64	57	52	48	59	54	50	46	56	51	48	45	41			
下方投影面積		cm ²	1.5	69	62	57	53	66	60	56	52	62	57	53	50	58	54	51	48	44				
等価発光面積		cm ²	2.0	73	67	62	58	70	65	61	57	66	61	58	55	62	58	55	53	48				
取付 高さ	器具間隔最大限		2.5	75	70	66	62	73	68	64	61	68	64	61	58	64	61	58	56	51				
	横方向 (A)		縦方向 (B)	3.0	77	72	69	65	74	70	67	64	70	66	64	61	65	63	60	58	54			
H m	1.31 H m	1.32 H m	4.0	79	75	72	69	77	73	70	68	72	69	67	65	68	65	63	62	57				
			5.0	80	77	75	72	78	75	73	70	73	71	69	67	69	67	65	64	59				
			7.0	82	80	78	76	80	78	76	74	75	73	72	70	71	69	68	67	61				
			10.0	83	82	80	78	81	79	78	76	76	75	74	73	72	71	70	69	63				

