

屋内照明器具特性	
品番 (品名)	LGB58082F
光源	LDA4L-G/S/K4 ×1 485.0 lm
管理番号	K0123318 (0) DR1
BZ分類	BZ4/0.7/BZ3/0.9/BZ4/3.5/BZ5

器具効率		93 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z CM
保守率		良 中 否	0.67	0.6	54	44	38	33	53	43	37	33	49	41	36	32	46	39	34	31	28
			0.63	0.8	63	54	47	42	61	52	46	42	57	50	45	41	54	48	43	39	36
			0.56	1.0	69	60	54	49	67	59	53	48	62	56	51	47	59	53	49	45	42
				1.25	74	66	60	55	71	64	58	54	67	61	56	52	63	58	54	50	47
下方投影面積		cm ²		1.5	77	70	64	59	75	68	63	58	70	64	60	56	66	61	57	54	50
			等価発光面積	cm ²	2.0	81	75	70	66	79	73	69	65	74	69	65	62	70	66	63	60
取付 高さ	器具間隔最大限		2.5	84	79	74	70	82	77	73	69	77	73	69	66	72	69	66	63	59	
	横方向 (A)	縦方向 (B)	3.0	86	81	77	74	84	79	75	72	79	75	72	69	74	71	68	66	61	
H m	1.31 H m	1.31 H m	4.0	89	85	81	78	86	82	79	76	81	78	75	73	76	74	72	70	64	
			5.0	90	87	84	81	88	85	82	79	83	80	78	76	78	76	74	72	67	
			7.0	92	89	87	85	89	87	85	83	84	82	81	79	80	78	77	75	69	
			10.0	93	92	90	88	91	89	88	86	86	84	83	82	81	80	79	78	72	

