

屋内照明器具特性	
品番 (品名)	L G W8 5 2 3 8 B
光源	LLD2000LCE1 ×1 531.0 lm
管理番号	K0180440 (0) DR 1
BZ分類	BZ5

器具効率		5 6 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		5 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束		5 1 %																				
保守率		良 中 否	0 . 6 3	0 . 6	3 1	2 4	1 9	1 6	3 0	2 3	1 9	1 6	2 8	2 2	1 8	1 6	2 6	2 1	1 8	1 5	1 4	
			0 . 6	0 . 8	3 6	2 9	2 5	2 2	3 5	2 9	2 5	2 1	3 3	2 8	2 4	2 1	3 1	2 6	2 3	2 0	1 9	
			0 . 5 6	1 . 0	4 0	3 4	2 9	2 6	3 8	3 3	2 9	2 5	3 6	3 1	2 8	2 5	3 4	3 0	2 7	2 4	2 2	
				1 . 2 5	4 3	3 7	3 3	3 0	4 2	3 6	3 2	2 9	3 9	3 5	3 1	2 9	3 7	3 3	3 0	2 8	2 6	
下方投影面積		c m ²		1 . 5	4 5	4 0	3 6	3 3	4 4	3 9	3 5	3 2	4 1	3 7	3 4	3 1	3 9	3 6	3 3	3 0	2 8	
等価発光面積			c m ²	2 . 0	4 8	4 4	4 0	3 7	4 7	4 3	4 0	3 7	4 4	4 1	3 8	3 6	4 2	3 9	3 7	3 5	3 2	
取付 高さ	器具間隔最大限		2 . 5	5 0	4 7	4 3	4 0	4 9	4 5	4 2	4 0	4 6	4 3	4 1	3 9	4 4	4 1	3 9	3 7	3 5		
	横方向 (A) 縦方向 (B)		3 . 0	5 2	4 8	4 5	4 3	5 0	4 7	4 5	4 2	4 8	4 5	4 3	4 1	4 5	4 3	4 1	3 9	3 7		
H m	1 . 2 5 H m	1 . 2 4 H m	4 . 0	5 4	5 1	4 8	4 6	5 2	5 0	4 7	4 5	5 0	4 7	4 6	4 4	4 7	4 5	4 4	4 2	4 0		
			5 . 0	5 5	5 2	5 0	4 8	5 3	5 1	4 9	4 7	5 1	4 9	4 7	4 6	4 8	4 7	4 5	4 4	4 1		
			7 . 0	5 6	5 4	5 3	5 1	5 5	5 3	5 2	5 0	5 2	5 1	5 0	4 8	5 0	4 9	4 8	4 7	4 4		
			1 0 . 0	5 7	5 6	5 5	5 3	5 6	5 5	5 3	5 2	5 3	5 2	5 1	5 0	5 1	5 0	4 9	4 8	4 6		

