

屋内照明器具特性	
品番 (品名)	L G W8 5 2 3 8 B
光源	LLD2020LCE1 ×1 460.0 lm
管理番号	K0180441 (0) DR 1
B Z 分類	BZ5

器具効率		51 % 上方光束 4 % 下方光束 47 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
			室指数	照明率 (X0.01) Z CM																	
保守率		良 中 否	0.63	0.6	28	21	17	14	27	21	17	14	25	20	17	14	24	19	16	14	12
			0.6	0.8	32	26	22	19	31	26	22	19	30	25	21	19	28	24	21	18	17
			0.56	1.0	36	30	26	23	35	29	25	22	32	28	25	22	31	27	24	21	20
				1.25	39	33	29	26	37	33	29	26	35	31	28	25	33	30	27	25	23
下方投影面積		cm ²		1.5	41	36	32	29	39	35	31	29	37	33	30	28	35	32	29	27	25
等価発光面積			cm ²	2.0	44	39	36	33	42	38	35	33	40	37	34	32	38	35	33	31	29
				2.5	45	42	39	36	44	41	38	36	42	39	37	34	40	37	35	33	31
取付 高さ	器具間隔最大限		3.0	47	43	41	38	45	42	40	38	43	41	38	37	41	39	37	35	33	
	横方向 (A)			縦方向 (B)		4.0	48	46	43	41	47	45	43	41	45	43	41	39	43	41	40
H m	1.20 H m	1.19 H m	5.0	49	47	45	43	48	46	44	43	46	44	43	41	44	43	41	40	38	
			7.0	51	49	47	46	50	48	47	45	47	46	45	44	45	44	43	42	40	
			10.0	52	50	49	48	51	49	48	47	48	47	47	46	46	46	45	44	42	

