

屋内照明器具特性	
品番 (品名)	L G W8 5 2 3 8 S
光源	L L D 3 0 2 0 M L C B 1 × 1 7 1 5 . 0 l m
管理番号	K 0 1 8 0 4 4 3 (0) D R 1
B Z 分類	B Z 5

器具効率		5 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 3	0 . 6	2 7	2 1	1 7	1 4	2 6	2 1	1 7	1 4	2 5	2 0	1 6	1 4	2 3	1 9	1 6	1 4	1 2
			0 . 6	0 . 8	3 2	2 6	2 2	1 9	3 1	2 5	2 2	1 9	2 9	2 4	2 1	1 8	2 7	2 3	2 0	1 8	1 6
			0 . 5 6	1 . 0	3 5	2 9	2 5	2 2	3 4	2 9	2 5	2 2	3 2	2 8	2 4	2 2	3 0	2 6	2 3	2 1	2 0
				1 . 2 5	3 8	3 3	2 9	2 6	3 7	3 2	2 8	2 6	3 5	3 1	2 7	2 5	3 3	2 9	2 7	2 4	2 3
下方投影面積		c m ²		1 . 5	4 0	3 5	3 2	2 9	3 9	3 4	3 1	2 8	3 7	3 3	3 0	2 7	3 5	3 1	2 9	2 7	2 5
			等価発光面積	c m ²	2 . 0	4 3	3 9	3 5	3 3	4 2	3 8	3 5	3 2	3 9	3 6	3 4	3 1	3 7	3 5	3 2	3 0
取付 高さ	器具間隔最大限			2 . 5	4 5	4 1	3 8	3 6	4 3	4 0	3 7	3 5	4 1	3 8	3 6	3 4	3 9	3 7	3 5	3 3	3 1
	横方向 (A) 縦方向 (B)			3 . 0	4 6	4 3	4 0	3 8	4 5	4 2	3 9	3 7	4 3	4 0	3 8	3 6	4 0	3 8	3 7	3 5	3 3
H m	1 . 2 0 H m	1 . 2 0 H m		4 . 0	4 8	4 5	4 3	4 1	4 6	4 4	4 2	4 0	4 4	4 2	4 0	3 9	4 2	4 1	3 9	3 8	3 5
				5 . 0	4 9	4 7	4 5	4 3	4 8	4 6	4 4	4 2	4 5	4 4	4 2	4 1	4 3	4 2	4 1	3 9	3 7
				7 . 0	5 0	4 8	4 7	4 5	4 9	4 7	4 6	4 5	4 7	4 5	4 4	4 3	4 5	4 4	4 3	4 2	3 9
				1 0 . 0	5 1	5 0	4 9	4 7	5 0	4 9	4 8	4 7	4 8	4 7	4 6	4 5	4 6	4 5	4 4	4 3	4 1

