

屋内照明器具特性	
品番 (品名)	L G W8 5 2 3 8 S
光源	LLD40001CQ1 ×1 845.0 l m
管理番号	K0180445 (0) DR 1
B Z 分類	B Z 5

器具効率		5 2 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
上方光束		5 %	室指数	照明率 (X 0 . 0 1)																			Z C M		
下方光束		4 7 %																							
保守率		良 中 否	0 . 6 3	0 . 6	2 8	2 2	1 8	1 5	2 7	2 1	1 8	1 5	2 6	2 0	1 7	1 4	2 4	2 0	1 6	1 4	1 3				
			0 . 6	0 . 8	3 3	2 7	2 3	2 0	3 2	2 7	2 3	2 0	3 0	2 5	2 2	1 9	2 8	2 4	2 1	1 9	1 7				
				1 . 0	3 7	3 1	2 7	2 4	3 6	3 0	2 6	2 3	3 3	2 9	2 5	2 3	3 1	2 7	2 5	2 2	2 0				
			0 . 5 6	1 . 2 5	4 0	3 4	3 0	2 7	3 8	3 4	3 0	2 7	3 6	3 2	2 9	2 6	3 4	3 1	2 8	2 6	2 4				
下方投影面積		c m ²	1 . 5	4 2	3 7	3 3	3 0	4 1	3 6	3 3	3 0	3 8	3 4	3 1	2 9	3 6	3 3	3 0	2 8	2 6					
			2 . 0	4 5	4 1	3 7	3 4	4 3	4 0	3 7	3 4	4 1	3 8	3 5	3 3	3 9	3 6	3 4	3 2	3 0					
取付高さ	器具間隔最大限		2 . 5	4 7	4 3	4 0	3 7	4 5	4 2	3 9	3 7	4 3	4 0	3 8	3 6	4 0	3 8	3 6	3 4	3 2					
	横方向 (A) 縦方向 (B)		3 . 0	4 8	4 5	4 2	4 0	4 7	4 4	4 1	3 9	4 4	4 2	4 0	3 8	4 2	4 0	3 8	3 6	3 4					
H m	1 . 2 5 H m	1 . 2 5 H m	4 . 0	5 0	4 7	4 5	4 3	4 8	4 6	4 4	4 2	4 6	4 4	4 2	4 0	4 3	4 2	4 0	3 9	3 7					
			5 . 0	5 1	4 8	4 6	4 5	4 9	4 7	4 6	4 4	4 7	4 5	4 4	4 2	4 5	4 3	4 2	4 1	3 8					
			7 . 0	5 2	5 0	4 9	4 7	5 1	4 9	4 8	4 6	4 8	4 7	4 6	4 5	4 6	4 5	4 4	4 3	4 0					
			1 0 . 0	5 3	5 2	5 0	4 9	5 2	5 0	4 9	4 8	4 9	4 8	4 7	4 7	4 7	4 6	4 5	4 5	4 2					

