

屋内照明器具特性	
品番 (品名)	L G W8 5 2 3 8 Y
光源	LLD3020LCE1 ×1 795.0 lm
管理番号	K0180442 (0) DR 1
B Z 分類	BZ5

器具効率		47 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束 下方光束		4 % 43 %	室指数	照明率 (X0.01) Z CM																		
保守率		良 中 否	0.63	0.6	25	19	16	13	24	19	15	13	23	18	15	13	21	17	15	12	11	
			0.6	0.8	29	24	20	17	29	23	20	17	27	22	19	17	25	21	19	16	15	
			0.56	1.0	32	27	23	21	31	27	23	20	30	25	22	20	28	24	22	19	18	
				1.25	35	30	27	24	34	30	26	23	32	28	25	23	30	27	24	22	21	
下方投影面積		cm ²	1.5	37	33	29	26	36	32	29	26	34	30	28	25	32	29	27	25	23		
等価発光面積		cm ²	2.0	40	36	33	30	38	35	32	30	36	33	31	29	34	32	30	28	26		
取付 高さ	器具間隔最大限		2.5	41	38	35	33	40	37	34	32	38	35	33	31	36	34	32	30	28		
	横方向 (A) 縦方向 (B)		3.0	42	40	37	35	41	39	36	34	39	37	35	33	37	35	34	32	30		
H m	1.20 H m	1.19 H m	4.0	44	42	40	38	43	41	39	37	41	39	37	36	39	37	36	35	33		
			5.0	45	43	41	39	44	42	40	39	42	40	39	38	40	39	37	36	34		
			7.0	46	45	43	42	45	44	42	41	43	42	41	40	41	40	39	38	36		
			10.0	47	46	45	44	46	45	44	43	44	43	42	42	42	41	41	40	38		

