

屋内照明器具特性	
品番 (品名)	L G W8 5 2 3 8 Y
光源	LLD20001CQ1 ×1 531.0 lm
管理番号	K0180444 (0) DR 1
B Z 分類	BZ5

器具効率		53 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01)																			Z	CM
保守率		良 中 否	0.63	0.6	2.9	2.2	1.8	1.5	2.8	2.2	1.8	1.5	2.6	2.1	1.7	1.5	2.5	2.0	1.7	1.4	1.3				
			0.6	0.8	3.4	2.8	2.3	2.0	3.3	2.7	2.3	2.0	3.1	2.6	2.2	2.0	2.9	2.5	2.2	1.9	1.8				
			0.56	1.0	3.7	3.2	2.7	2.4	3.6	3.1	2.7	2.4	3.4	2.9	2.6	2.3	3.2	2.8	2.5	2.3	2.1				
				1.25	4.0	3.5	3.1	2.8	3.9	3.4	3.0	2.8	3.7	3.3	2.9	2.7	3.5	3.1	2.8	2.6	2.4				
下方投影面積		cm ²	1.5	4.3	3.8	3.4	3.1	4.1	3.7	3.3	3.0	3.9	3.5	3.2	2.9	3.7	3.3	3.1	2.9	2.7					
			2.0	4.6	4.1	3.8	3.5	4.4	4.0	3.7	3.5	4.2	3.9	3.6	3.3	3.9	3.7	3.4	3.2	3.0					
取付高さ	器具間隔最大限		2.5	4.7	4.4	4.1	3.8	4.6	4.3	4.0	3.7	4.4	4.1	3.8	3.6	4.1	3.9	3.7	3.5	3.3					
	横方向 (A) 縦方向 (B)		3.0	4.9	4.6	4.3	4.0	4.7	4.4	4.2	4.0	4.5	4.2	4.0	3.8	4.3	4.1	3.9	3.7	3.5					
H m	1.25 H m	1.25 H m	4.0	5.0	4.8	4.6	4.3	4.9	4.7	4.5	4.3	4.7	4.5	4.3	4.1	4.4	4.3	4.1	4.0	3.7					
			5.0	5.2	4.9	4.7	4.6	5.0	4.8	4.6	4.5	4.8	4.6	4.5	4.3	4.5	4.4	4.3	4.2	3.9					
			7.0	5.3	5.1	5.0	4.8	5.2	5.0	4.9	4.7	4.9	4.8	4.7	4.5	4.7	4.6	4.5	4.4	4.1					
			10.0	5.4	5.3	5.1	5.0	5.3	5.1	5.0	4.9	5.0	4.9	4.8	4.7	4.8	4.7	4.6	4.6	4.3					

