

屋内照明器具特性	
品番 (品名)	L G W8 5 2 3 9 S
光源	LLD6300LCF1 ×1 1270.0 lm
管理番号	K0180434 (0) DR 1
BZ分類	BZ6

器具効率		7 2 % 上方光束 1 2 % 下方光束 6 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
				室指数	照明率 (X 0 . 0 1) Z C M																				
保守率		良 中 否	0 . 6 3	0 . 6	0 . 5 6	0 . 6	3 7	2 8	2 2	1 8	3 6	2 7	2 2	1 8	3 3	2 6	2 1	1 7	3 0	2 4	2 0	1 7	1 4		
			0 . 6	0 . 8	4 4	3 5	2 9	2 5	4 2	3 4	2 9	2 5	3 9	3 2	2 7	2 3	3 6	3 0	2 6	2 2	2 0				
			0 . 5 6	1 . 0	4 9	4 0	3 5	3 0	4 7	3 9	3 4	2 9	4 3	3 7	3 2	2 8	3 9	3 4	3 0	2 7	2 4				
			1 . 2 5	5 3	4 5	4 0	3 5	5 1	4 4	3 8	3 4	4 7	4 1	3 6	3 3	4 3	3 8	3 4	3 1	2 8					
下方投影面積		c m ²	1 . 5	5 6	4 9	4 3	3 9	5 4	4 7	4 2	3 8	4 9	4 4	4 0	3 6	4 6	4 1	3 8	3 4	3 1					
			2 . 0	6 0	5 4	4 9	4 5	5 8	5 2	4 8	4 4	5 3	4 9	4 5	4 2	4 9	4 6	4 2	4 0	3 6					
等価発光面積		c m ²	2 . 5	6 3	5 7	5 3	4 9	6 0	5 5	5 1	4 8	5 6	5 2	4 8	4 5	5 2	4 8	4 6	4 3	3 9					
			3 . 0	6 4	6 0	5 6	5 2	6 2	5 8	5 4	5 1	5 8	5 4	5 1	4 8	5 3	5 1	4 8	4 6	4 1					
H m	1 . 3 7 H m	1 . 3 7 H m	4 . 0	6 7	6 3	6 0	5 7	6 5	6 1	5 8	5 5	6 0	5 7	5 5	5 2	5 6	5 4	5 1	4 9	4 5					
			5 . 0	6 8	6 5	6 2	6 0	6 6	6 3	6 0	5 8	6 2	5 9	5 7	5 5	5 7	5 5	5 4	5 2	4 7					
			7 . 0	7 0	6 8	6 5	6 3	6 8	6 6	6 3	6 1	6 3	6 2	6 0	5 8	5 9	5 8	5 6	5 5	5 0					
			1 0 . 0	7 2	7 0	6 8	6 6	6 9	6 8	6 6	6 4	6 5	6 4	6 2	6 1	6 1	6 0	5 9	5 7	5 2					

