

屋内照明器具特性	
品番 (品名)	L G W8 5 2 3 9 S
光源	L L D 2 0 2 0 L C E 1 × 1 4 6 0 . 0 1 m
管理番号	K 0 1 8 0 4 3 6 (0) D R 1
B Z 分類	B Z 5

器具効率		51 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %					10 %					10 %					10 %					0 %
上方光束 下方光束		4 % 47 %	室指数	照明率 (X0.01) ZCM																					
保守率		良 中 否	0.63	0.6	28	21	17	15	27	21	17	14	25	20	17	14	24	19	16	14	13				
			0.6	0.8	32	26	22	19	31	26	22	19	30	25	21	19	28	24	21	18	17				
			0.56	1.0	36	30	26	23	35	29	25	23	33	28	25	22	31	27	24	22	20				
				1.25	39	33	29	26	37	33	29	26	35	31	28	25	33	30	27	25	23				
下方投影面積		cm ²	1.5	41	36	32	29	40	35	32	29	37	34	30	28	35	32	29	27	25					
等価発光面積		cm ²	2.0	44	39	36	33	42	39	35	33	40	37	34	32	38	35	33	31	29					
取付 高さ	器具間隔最大限		2.5	45	42	39	36	44	41	38	36	42	39	37	35	40	37	35	34	32					
	横方向 (A) 縦方向 (B)		3.0	47	44	41	38	46	43	40	38	43	41	39	37	41	39	37	36	33					
H m	1.19 H m	1.19 H m	4.0	48	46	44	42	47	45	43	41	45	43	41	40	43	41	40	38	36					
			5.0	49	47	45	44	48	46	45	43	46	44	43	41	44	43	41	40	38					
			7.0	51	49	48	46	50	48	47	45	47	46	45	44	45	44	43	42	40					
			10.0	52	50	49	48	51	49	48	47	48	48	47	46	46	46	45	44	42					

