

屋内照明器具特性	
品番 (品名)	L G W8 5 2 3 9 Y
光源	LLD2000LCE1 ×1 531.0 lm
管理番号	K0180435 (0) DR 1
B Z 分類	BZ5

器具効率		56 % 上方光束 5 % 下方光束 51 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
			室指数	照明率 (X0.01) Z CM																	
保守率		良 中 否	0.63	0.6	31	24	20	17	30	23	19	16	28	22	19	16	26	22	18	16	14
			0.6	0.8	36	30	25	22	35	29	25	22	33	28	24	21	31	27	23	21	19
			0.56	1.0	40	34	29	26	39	33	29	26	36	32	28	25	34	30	27	24	23
				1.25	43	38	33	30	42	37	33	30	39	35	32	29	37	33	31	28	26
下方投影面積		cm ²		1.5	45	40	36	33	44	39	36	33	42	38	34	32	39	36	33	31	29
等価発光面積			cm ²	2.0	49	44	41	38	47	43	40	37	45	41	38	36	42	39	37	35	33
				2.5	51	47	44	41	49	46	43	40	47	44	41	39	44	42	40	38	35
取付高さ	器具間隔最大限		3.0	52	49	46	43	51	47	45	42	48	45	43	41	46	43	41	40	37	
	横方向 (A)			5.0	55	53	50	49	54	51	50	48	51	49	48	46	49	47	46	45	42
	縦方向 (B)		7.0	56	54	53	51	55	53	52	50	52	51	50	49	50	49	48	47	44	
H m	1.24 H m	1.25 H m	10.0	57	56	55	54	56	55	54	53	53	52	51	51	51	50	49	49	46	

