

屋内照明器具特性	
品番 (品名)	NNN13600BK
光源	LDA13L-G/Z100E/S/W ×1 1520.0 lm
管理番号	K0179315 (1) DB1
BZ分類	BZ3

器具効率		23 %	反射率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		0 %	室指数	照明率 (X0.01)																			Z	C	M
下方光束		23 %																							
保守率		良 中 否	0.63	0.6	14	12	10	9	14	12	10	9	13	11	10	9	13	11	10	9	8				
			0.6	0.8	17	14	13	12	16	14	13	12	16	14	13	12	15	14	12	12	11				
			0.56	1.0	18	16	15	14	18	16	15	14	17	16	14	13	17	15	14	13	13				
			1.25	1.9	18	16	15	19	17	16	15	19	17	16	15	18	17	16	15	15					
下方投影面積 等価発光面積		cm ² cm ²	1.5	2.0	2.1	2.0	1.9	1.8	2.1	2.0	1.9	1.8	2.1	2.0	1.9	1.8	2.0	1.9	1.8	1.8	1.7				
			2.5	2.2	2.1	2.0	1.9	2.2	2.1	2.0	1.9	2.1	2.0	2.0	1.9	2.1	2.0	1.9	1.9	1.8					
			3.0	2.3	2.2	2.1	2.0	2.2	2.1	2.1	2.0	2.2	2.1	2.0	2.0	2.1	2.0	2.0	1.9	1.9					
H	m	1.14 H	m	1.58 H	m	4.0	2.3	2.2	2.2	2.1	2.3	2.2	2.2	2.1	2.2	2.1	2.1	2.0	2.0						
			5.0	2.3	2.3	2.2	2.2	2.3	2.3	2.2	2.2	2.3	2.2	2.2	2.1	2.2	2.2	2.1	2.1	2.0					
			7.0	2.4	2.3	2.3	2.3	2.3	2.3	2.3	2.2	2.3	2.3	2.2	2.2	2.2	2.2	2.2	2.2	2.1					
			10.0	2.4	2.4	2.3	2.3	2.4	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.2	2.2	2.2	2.1					

