

屋内照明器具特性	
品番 (品名)	NNN13600BK
光源	LDA7L-G/S/K6 ×1 810.0 lm
管理番号	K0179314 (1) DB1
BZ分類	BZ2/8.5/BZ1

器具効率		28 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
上方光束		0 %	室指数	照明率 (X0.01)																			Z CM
下方光束		28 %																					
保守率		良 中 否	0.63	0.6	19	16	15	14	19	16	15	13	18	16	15	13	18	16	14	13	13		
			0.6	0.8	22	19	18	17	21	19	18	17	21	19	18	17	20	19	17	16	16		
			0.56	1.0	23	21	20	19	23	21	20	19	23	21	20	19	22	20	19	19	18		
				1.25	25	23	22	21	24	23	22	21	24	22	21	20	23	22	21	20	20		
下方投影面積		cm ²	1.5	26	24	23	22	25	24	23	22	25	23	22	22	24	23	22	21	21			
等価発光面積		cm ²	2.0	27	26	24	24	26	25	24	23	26	25	24	23	25	24	24	23	22			
取付 高さ	器具間隔最大限		2.5	28	26	26	25	27	26	25	25	27	26	25	24	26	25	25	24	23			
	横方向 (A)		縦方向 (B)	3.0	28	27	26	26	28	27	26	25	27	26	26	25	26	26	25	25	24		
H m	1.00 H m	1.34 H m	4.0	29	28	27	27	28	27	27	26	28	27	26	26	27	26	26	26	25			
			5.0	29	28	28	27	28	28	27	27	28	27	27	27	27	27	26	26	25			
			7.0	29	29	28	28	29	28	28	28	28	28	28	27	28	27	27	27	26			
			10.0	29	29	29	29	29	29	29	28	28	28	28	28	28	28	27	27	27			

